TOWNSHIP 27 RANGE 02 POINT IDENTIFIER # 138500

PRIMARY CORNER DESCRIPTION South 1/4 Cor. Sec. 7 only

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Charles Roberts, US Deputy Surveyor under contract #759 dated Oct. 26, 1904 - (DCSO records Vol. 12 Page(s) 4894)

Set a basalt stone 14x8x6", 10" in the ground for ¼ sec. cor. mkd. ¼ on N face, from which
A fir, 12" dia., bears N.20½°E., 25 lks., mkd: ¼ S7 BT.
A fir, 15" dia., bears S.31°E., 42 lks., mkd: ¼ S18 BT.

GLO resurvey by Morris Wygant, Compass man for Zachariah M. Derrick U.S. Dep. Surveyor, under contract #779, dated Feb. 7, 1908 - (DCSO records Vol. 12 Page(s) 4916)

The ¼ sec. cor. which is a stone, firmly set, marked & witnessed as described by the surveyor general & which I now change to refer to sec. 7 only.

Douglas Co. Surveyors Office - John Powell - Frank Jones - W. Penley - Oct. 1969 - C.S. File 54/40-186

Found - 14x8x6" Stone, firmly set r&d: "¼" on north face.
12" D.Fir, now snag, N.20½°E. 16.5 ft., shows good scar.
15", now 24" D.Fir, S.31°E. 27.7 ft. shows good scar
Set - Brass Cap at Cor. Mkd: COUNTY SURVEYORS OFFICE 1969 T27S R2W ¼ S 7
New BTs- 15" W.Fir N.9°W. 34.3 ft. mkd: ¼ S 7 CS BT.
24" D.Fir N.57°W. 33.7 ft. mkd: ¼ S 7 CS BT.
This corner lies about 85 ft. E. of spring branch, course north.

Fd. & used on BLM Dependent resurvey by Wayne Rogers, Cadastral Surveyor, under Group #983, surveyed May/Aug 1979 - (DCSO records Vol. 44 Page(s) 16929-30)

Fd. Ok by K.DeGroot 4/1990 - M109-79