TOWNSHIP 27 RANGE 02 POINT IDENTIFIER # 140300

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 19 & 30

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO resurvey by Morris Wygant, Compass man for Zachariah M. Derrick U.S. Dep. Surveyor, under contract #779, dated Feb. 7, 1908 - (DCSO records Vol. 12 Page(s) 4955)

West bet. Secs. 19 & 30 40.00 chs.
Set a cedar post, 3 ft. long, 4" sq., 24" in the ground, for ¼ sec. cor., marked ¼ S19 on N & 30 on S face; from which
A fir, 8" dia., bears S.0°30'E., 31 lks., mkd: ¼ S30 BT.
A fir, 8" dia., bears N.31°W., 22 lks., mkd: ¼ S19 BT.
42.00 chs.
Derricks ¼ sec. cor. which I now destroy, bears N.300 lks.
Note - We have no record of Derrick setting this corner.
JC DCSO 9/2008

Douglas Co. Surveyors Office - Vernon "Ray" Tracy - Frank Jones - V. Perron - Nov. 1968 - C.S. File 54/40-132

Found - Orig. 8",now 25" Fir, alive, S.0°30'E., 20.5 ft., open & find "S30"
Orig. 8" now 30" Fir, N.31°W. 14.5 ft., alive, shows faint scar. Rescribe: "¼ S19 CS BT"
Set - Brass Cap at Cor. mkd: COUNTY SURVEYORS T27S R2W
OFFICE ¼ S 19
1968 S 30
New BT - 18" D.Fir S.37°E. 28.0 ft. mkd: ¼ S30 CS BT
This corner lies on top of ridge sloping north.

Fd. Ok by Ron Geisler, 8/1985 - M90-71

BLM dependent resurvey by A. Bert Skeesick & Timothy J Moore, Cadastral Surveyors & Robert H Browning, Survey Technician, under Group No. 1968, surveyed Aug. 2003/July 2004 - (DCSO records Vol. 56 Page(s) 22019-20)

The ¼ sec. cor. of secs. 19 and 30, remonumented by the Douglas County Surveyors Office in 1968, monumented with an iron post, 1¼" dia., firmly set, projecting 9" above ground, with brass cap (properly) mkd.
from which the original bearing trees
A fir, 30" dia., bears S.1/2°E., 20.5 ft., with a healed blaze.
A fir, 35" dia., bears N.31°W., 14.5 ft., with a healed blaze. (Rescribed by the Douglas Co. Surveyors Office)
and bearing tree mkd. by the Douglas County Surveyors Office
A fir, 21" dia. bears S.39°E. 27.3 ft. with a healed blaze
The geographic position (NAD 1983 (CORS 2000)) of the 1/4 section corner of sections 19 and 30, was determined by a direct tie to a temporary point for which a position **CONT**.

TOWNSHIP 27 RANGE 02 POINT IDENTIFIER # 140300

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 19 & 30

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

... had been determined, to an accuracy level of 0.050 meters or better, 95% confidence level, relative to the National Spatial Reference System, noted above, is as follows:
Latitude: 43°11'53.49"N. Longitude: 122°58'50.68"W.