

TOWNSHIP 27 RANGE 02 POINT IDENTIFIER # 140600

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 6 & 7

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO Survey by Samuel C. Flint, Under Contract #459, dated Aug. 3, 1882 (DCSO Records Vol. 12 Page(s) 4884)

Set laurel post, 3 ft. long, 3" sq., 24" in the ground, for 1/4 sec. cor., marked 1/4 S on N & S faces; from which
A fir, 30" dia., bears South, 5 lks., mkd: 1/4 S BT.
A fir, 36" dia., bears N.40°W., 35 lks., mkd: 1/4 S BT.

FD on GLO survey by Charles Roberts, US Deputy Surveyor under contract #759 dated Oct. 26, 1904 - (DCSO records Vol. 12 Page(s) 4901)

Douglas Co. Surveyors Office - Vernon "Ray" Tracy - Frank Jones - V. Perron - Nov. 1968 - C.S. File 54/40-135

Found - Orig. 36" now 44" Fir, alive, N.40°W., 23.1 ft., bark scribe visible.
Orig. 30" Fir now down & badly decayed, South 3.3 ft
Set Brass cap at cor. mkd: COUNTY SURVEYORS T27S R2W
OFFICE 1/4 S 6
1968 S 7

New BTs- 15" D.Fir N.81°W., 59.8 ft. mkd: 1/4 S6 CS BT
9" D.Fir S.20°W., 53.5 ft. mkd: 1/4 S7 CS BT
This corner lies on steep southerly slope on N-S cutting line, cut off to E.

BLM Dependent resurvey by Wayne Rogers, Cadastral Surveyor, under Group #983, surveyed May/Aug 1979 - (DCSO records Vol. 44 Page(s) 16917-8)

The 1/4 sec. cor. of secs. 6 & 7, perpetuated & recorded by Tracy in 1968, monumented w/an iron post 1 1/4" dia. firmly set, projecting 12" above ground, with brass cap (properly) mkd from which the remains of the orig. BTs
A root hole, bears South, 5 lks., with down fir alongside, size indeterminate, no marks visible.
A fir, 45" dia., bears N.40°W., 35 lks., with scribe marks 1/4 S BT visible on bark.
and a BT mkd. by Tracy
A fir 18" dia., bears N.81°W., 90 lks., with healed double blaze.
and a new BTs
A fir, 5" dia., bears S.69 3/4°E., 46 lks., mkd: X BT.