

TOWNSHIP 27 RANGE 02 POINT IDENTIFIER # 176100

PRIMARY CORNER DESCRIPTION A P on So. bdy. Sec. 31

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by S.C. Flint, Contract #459, dated August 3, 1882
- (DCSO records Vol. 12 Page(s) 4863)

Set Cedar post 4 ft. long, 4" sq., 24" in the ground for
standard cor. to secs. 31 and 32, marked T27S R2W on N.; S32
on E.; and S31 on W. faces, with 5 notches on the E., 1 on
the W. edges, from which

A Fir 24" dia., bears N.15°E., 38 lks. dist. mkd. T27S R2W
S32 BT.

A Fir 30" dia., bears N.50°W., 17 lks. dist. mkd. T27S R2W
S31 BT.

A Fir 30" dia., bears S.47°W., 25 lks. dist. mkd. T28S R2W
S6 BT.

GLO Resurvey by Morris Wygant, Compassman for Zachariah
Derrick, U.S. Deputy Surveyor, Under Contract #779, dated
Feb. 7, 1908 - (DCSO records Vol. 12 Page(s) 4906)

The standard cor. of secs. 31 and 32, which is a post, firmly
set, marked and witnessed as described by the surveyor
general, bears S. 100 lks. dist. I now change this cor. to
an Angle Pont as follows:

Cut out all marks and mark AP on N. face; then cut out all
BTs and remark AP BT.

Survey by Thomas E. Shrum, Jr. - For: U.S. Plywood - Dec.
1968 - M 37-17

Set 2½" Alum. cap mkd. "A.P. T27S R2W S6 S31 T28S", from
which

6" Madrone N.03°W., 27.7 ft. mkd. "A.P. S31 BT RE 4287".

6" D.Fir S.43°W., 23.1 ft. mkd. "A.P. S6 BT RE 4287".

Survey by Romano E. Ware and Ronald A. Quimby - For: U.S.
Forest Service - July 1980 - M 79-49

Found - 1" I.P. with alum. cap mkd. "US PC Prop. Cor. T27S
R2W AP 31 6 T28S R2W RE 4287 1968".

8" Madrone N.3°W., 27.7 ft. visible scribes.

6" D.Fir S.43°W., 23.1 ft. visible scribes.

Set Fiberglass post with signs 54.2 ft. and 54.4 ft. East.