

PRIMARY CORNER DESCRIPTION CC Secs. 7 & 8 only, South

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Charles Roberts, US Deputy Surveyor under contract #759 dated Oct. 26, 1904 - (DCSO records Vol. 12 Page(s) 4893)

Set a basalt stone 14x10x7", 10" in the ground for cor. of secs. 7, 8, 17, & 18 mkd with 4 notches on S & 5 notches on E edge, from which

A fir, 30" dia. bears N.47½°E. 50 lks. mkd: T27S R2W S8 BT
A fir, 18" dia. bears S.47°E. 43 lks. mkd: T27S R2W S17 BT
A fir, 22" dia. bears S.30°W. 34 lks. mkd: T27S R2W S18 BT
A fir, 18" dia. bears N.14°W. 122 lks. mkd: T27S R2W S7 BT

GLO resurvey by Morris Wygant, Compass man for Zachariah M. Derrick U.S. Dep. Surveyor, under contract #779, dated Feb. 7, 1908 - (DCSO records Vol. 12 Page(s) 4916)

The cor. of secs. 7, 8, 17, & 18 which is a stone, firmly set, marked & witnessed as described by the surveyor general & which I now change to refer to secs. 7 & 8 only bears South 139 lks. The course of this line from the ¼ sec. cor. is S.87°37'W., and the length is 40.68 chs. (S¼ S8)

Douglas Co. Surveyors Office - John Powell - Frank Jones - W. Penley - Oct. 1969 - C.S. File 54/40-183

Found - 14x10x7 Stone, firmly set, mkd with notches as noted 30", now 42" D.Fir, N.47½°E. 33.0 ft., tree opened & burnt, scribe vis.
18" D.Fir, now stump, N.14°W., 80.5 ft., found burnt reverse scribe.

Set - Brass Cap at Car. Mkd: COUNTY SURVEYORS T27S R2W
OFFICE S 7|S 8
1969 S 18

New BTs- 16" Hemlock N.44°W. 23.9 ft. mkd: T27S R2W S7 CS BT
33" D.Fir S.22°E. 17.0 ft. mkd: T27S R2W S18 CS BT.
42" D.Fir N.47°E. 33.0 ft. mkd: T27S R2W S8 CS BT
(Reblazed & rescribed)

Dependent resurvey by Peter A. Peterson & Daniel L. Berry, Cadastral Surveyors, under Group No. 757, surveyed Aug./Sept. 1971 - (DCSO Records Vol. 35 Page(s) 14594-5)

The cor. of secs. 7 & 8 only, perpetuated & recorded by Powell in 1969, monumented with an iron post, 1" dia., firmly set, protruding 13" above ground, with brass cap (properly) mkd. alongside of which is the orig. basalt stone, 14x10x7" loosely set 2" in the ground, marked with 4 notches on S & 5 notches on E edge,

continued next page

TOWNSHIP 27 RANGE 02 POINT IDENTIFIER # 176500

PRIMARY CORNER DESCRIPTION CC Secs. 7 & 8 only, South

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

from which the remaining orig. BTs

- A fir, 50" dia., bears N.47½°E., 50 lks., with axe marks visible on weathered bark blaze; remarked by Powell in 1969, with healed blaze.
- A root hole, bears S.47°E., 43 lks., with a down fir alongside, 30" dia., with healed blaze.
- A fir stump, 18" dia., bears N.14°W., 122 lks., with illegible scribe marks visible on opened blaze.

and trees mkd by Powell in 1969

- A fir, 35" dia., bears S.22°E., 26 lks., with healed double blaze.
- A hemlock, 16" dia., bears N.45°W., 36 lks., with scribe marks T27S R2W S7 CS BT visible on partially healed double blaze.

Fd. Ok by D. Edwards, 9/1998 - M130-47