

TOWNSHIP 27 RANGE 02 POINT IDENTIFIER # 177100

PRIMARY CORNER DESCRIPTION C C for Secs. 5 & 6 only, T28-2

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by William N. Gibb, Deputy Surveyor, under Contract #783, dated Dec. 3, 1908 - (DCSO records Vol. 13 Page(s) 5478¼)

-----  
Intersect N. bdy. Tp. 10 lks. E. of cor. secs. 31 & 32.  
Now at point of intersection, Set Fir post 3 ft. long, 4" sq., 24" in the ground for closing cor. secs. 5 & 6 mkd. CC T28S R2W on S.; S5 on E.; and S6 on W. face, with 5 grooves on E. and 1 groove on W. face, from which  
A Fir 3" dia., bears S.57°E., 81 lks. dist. mkd. T28S R2W S5 BT.  
A Fir 4" dia., bears S.45°W., 9 lks. dist. mkd. T28S R2W S6 BT

Douglas Co. Surveyors Office - Milo E. Godfrey, Deputy - Vernon Tracy; M. Stone, crew - Sept. 1962 - C.S. 49/28-11

-----  
Found - Fir now 42", bark scribing visible. (Orig. must have been 40" instead of 4"), S.45°W., 6.0 ft. from face.  
Fir now 48" S.34°E., (Not S.57°E.), 53.5 ft. (face) bark scribing visible. (Orig. must have been 30" instead of 3".)  
Set Brass cap at cor. mkd: County Surveyors Office  
T28S R2W  
CC S6 | S5  
1962  
Orig. BTs-42" D.Fir bears S.45°W., 7.2 ft. to center of tree.  
48" D.Fir bears S.34°E., 55.5 ft. to center of tree

Douglas County Surveyors Office - Vernon "Ray" Tracy and crew Nov. 1968 - C.S. File 54/40-123

-----  
Found - Brass cap mkd. in 1962.  
42" D.Fir now 43", S.45°W., 7.2 ft. shows bark scribing.  
48" now 49" D.Fir S.34°W., 55.5 ft. shows bark scribing. (Rec. is SE. Tracy's field notes read SW.)  
Remark Brass cap to read: County Surveyors Office 1968  
T27S R2W C.C. S6 | S5  
T28S  
Rescribed 49" D.Fir S.34°W., 55.5 ft. "T28S R2W S5 CC CS BT"  
New BT - 6" Madrone S.1°W., 44.0 ft. "T28S R2W S6 CC CS BT."  
Corner lies N.85°E., 7.0 ft. of A.P. secs. 31 and 6, and 226.9 ft. of cor. secs. 31 and 32, T27-2

TOWNSHIP 27 RANGE 02 POINT IDENTIFIER # 177100

PRIMARY CORNER DESCRIPTION C C for secs. 5 & 6 only, T28-2

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Survey by Romanso E. Ware and Ronald A. Quimby - For: U.S. Forest Service - July 1980 - M 79-49

-----  
Found - 1½" I.P. with brass cap as mkd. in 1968.  
50" D.Fir S.34°E., 55.5 ft., visible scribes.  
44" D.Fir S.45°W., 7.2 ft., good scar.  
8" Madrona, S.1°W., 44.0 ft. visible scribes.  
Set Fiberglass post and signs 4.0 ft. South.

BLM dependent resurvey by A. Bert Skeesick & Timothy J Moore, Cadastral Surveyors & Robert H Browning, Survey Technician, under Group No. 1968, surveyed Aug. 2003/July 2004 - (DCS0 records Vol. 56 Page(s) 21984-5)

-----  
The orig. closing cor. of secs. 5 & 6, T28S R2W bears S.89°32'15"W., 223.76 ft.; remonumented by the Douglas County Surveyors Office in 1962, perpetuated by the Douglas County Surveyors Office in 1968, monumented with an iron post, 1¼" dia., firmly set, projecting 6" above ground, with brass cap (properly) mkd.  
from which the remains of the original bearing trees  
A fir, 42" dia., bears S.32¾°E., 55.6 ft., with a healed blaze. (Record, S.57°E., 53.5 ft.)  
A fir, 46" dia., bears S.36¼°W., 7.2 ft., with a no marks visible on an opened, decayed blaze. (Record, S.45°W., 5.94 ft.)  
and a BT mkd. by the Douglas County Surveyors Office in 1968  
A madrone, 8" dia., bears S.1¼°W., 43.7 ft., with fragmentary scribe marks visible on a partially healed blaze.