

TOWNSHIP 27 RANGE 02 POINT IDENTIFIER # 200100

PRIMARY CORNER DESCRIPTION C C for Secs. 31 and 32 only (South)

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GL0 Resurvey by Morris Wygant, Compassman for Zachariah Derrick, U.S. Deputy Surveyor, Under Contract #779, dated Feb. 7, 1908 - (DCSO records Vol. 12 Page(s) 4952-53)

-----  
Intersect S. bdy. of Tp. 350 lks. N.88°57'E. of the old cor. of secs. 31 and 32, which I previously changed to an Angle Point.

At point of intersection, I Set a Laurel post, 3 ft. long, 4" sq., 24" in the ground, for closing cor. of secs. 31 and 32, marked T27S R2W on N.; S32 on E.; and S31 on W.; with 5 grooves on E. and 1 groove on W. face, from which

A Fir 24" dia., bears N.29°30'E., 10 lks. dist. mkd. T27S R2W S32 BT.

A Fir 24" dia., bears N.21°W., 85 lks. dit. mkd. T27S R2W S31 BT.

Douglas Co. Surveyors Office - Milo E. Godfrey, Deputy - Vernon Tracy; M. Stone, crew - Sept. 1962 - C.S. 49/28-12

-----  
Found - Unrecorded 1½" Iron pipe in mound of rock at corner. Rotten Fir snag, N.29½°E., 6.6 ft., good scribing on piece of rotten Fir wood lying at base of snag, "T27S R2W S32 BT"

D.Fir, alive and standing, now 28" bears N.21°W., 56.1 ft., shows good axe scar. In small opening previously made, found good scribing "B".

Did Not Set Brass Cap at Corner.

New BTs- 10" D.Fir N.12°W., 14.7 ft. mkd. T27S R2W S31 CS BT

6" Madrone N.78°E., 21.4 ft. mkd. T27S R2W S32 CSBT

Cor. lies on top of rocky ridge sloping South.

Douglas County Surveyors Office - Vernon "Ray" Tracy and crew Nov. 1968 - C.S. File 54/40-122

-----  
Found - 1/2" I.Pipe.  
10" now 12" D.Fir N.12°W., 14.7 ft., shows scribing.  
6" now 7" madrone N.78°E., 21.4 ft., shows scribing.

Set Brass cap at cor. mkd: County Surveyors Office  
T27S R2W CC S 31 | S 32  
T28S 1968

This corner lies on top of rocky ridge sloping South and lies East 226.9 ft. of C.C. secs. 5 & 6, T28-2W.

Survey by Romanso E. Ware and Ronald Quimby - For: U.S. Forest Service - July 1980 - M 79-49

-----  
Found - 1968 DCSO brass cap, properly marked.  
(Cont. Next Page)

TOWNSHIP 27 RANGE 02 POINT IDENTIFIER # 200100

PRIMARY CORNER DESCRIPTION C C for secs. 31 & 32 only (South)

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

6" Madrona, N.78°E., 21.4 ft., visible scribes.  
12" D.Fir, N.12°W., 14.7 ft., good scar.  
Set Fiberglass post and sign 3.0 ft. North of corner.

BLM dependent resurvey by A. Bert Skeesick & Timothy J Moore, Cadastral Surveyors & Robert H Browning, Survey Technician, under Group No. 1968, surveyed Aug. 2003/July 2004 - (DCSO records Vol. 56 Page(s) 21984)

-----  
The closing cor. of secs. 31 and 32 only, on the S. bdy. of the Tp., perpetuated by the Douglas County Surveyors Office in 1962 and remonumented by the Douglas County Surveyors Office in 1968, monumented with an iron post, 1¼" dia., firmly set, projecting 18" above ground, in a mound of stone, 3 ft. base to top, with brass cap (properly) mkd.

- from which the remains of the original bearing trees
- A decayed fir stump, size indeterminate, bears N.25¼°E., 7.7 ft., with no marks visible. (Record, N.29°30'E., 6.6 ft.)
  - A fir stump, 28" dia., bears N.23°W., 57.5 ft., with a partially healed blaze. (Record, N.21°W., 56.1 ft.)
- and BTs mkd. by the Douglas County Surveyors Office in 1968
- A madrone, 8" dia., bears N.78°E., 20.9 ft., with fragmentary scribe marks visible on a partially healed blaze.
  - A fir, 21" dia., bears N.12¾°W., 15.1 ft., with a healed blaze.