

TOWNSHIP 27 RANGE 02 POINT IDENTIFIER # 200300

PRIMARY CORNER DESCRIPTION Cor Secs 19, 20, 29, & 30

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GL0 resurvey by Morris Wygant, Compass man for Zachariah M. Derrick U.S. Dep. Surveyor, under contract #779, dated Feb. 7, 1908 - (DCSO records Vol. 12 Page(s) 4953-4)  
-----  
Set a cedar post, 3 ft. long, 4" sq., 24" in the ground for cor. to secs. 19, 20, 29, & 30, marked T27S S 20 on NE, R2W S 29 on SE, S 30 on SW, S 19 on NW faces, with 2 notches on S & 5 notches on E edges; from which  
    A cedar, 12" dia., bears N.48°10'E., 37 lks., mkd: T27S R2W S20 BT.  
    A fir, 12" dia., bears S.64°10'E., 27 lks., mkd: T27S R2W S29 BT.  
    A cedar, 12" dia., bears S.62°10'W., 40 lks., mkd: T27S R2W S30 BT.  
    A fir, 10" dia., bears N.31°W., 12 lks., mkd: T27S R2W S19 BT.  
Derricks cor. for secs. 19, 20, 29, & 30 which I now destroy bears N.42°W., 450 lks.

Douglas Co. Surveyors Office - Milo E. Godfrey & crew - Nov. 1964 - C.S. File 49/28-23  
-----  
Found - 12" fir snag N.31°W., 7.9 ft. cut open & fd. good scribing.  
        17" Cedar N.48°E., 24.4 ft. shows good scar, good condition.  
        19" Fir S.64°E., 17.8 ft. shows good scar, tree in good condition.  
        20" Cedar S.62°W., 26.4 ft. shows good scar, tree in good condition.  
Set - Brass cap at cor mkd: COUNTY SURVEYORS T27S R2W S19|S22 OFFICE 1964 S30|S29  
New BT - 31" Hemlock N.22°W. 36.0 ft. mkd: T27S R2W S19 CS BT  
Corner is approx. 200 ft. S of centerline of Wolf Creek access Rd.

Fd. Ok - Douglas Co. Surveyors Office - Vernon "Ray" Tracy Nov. 1968 - C.S. File 54/40-133

Ronald G. Geisler, Champion International - June/Aug 1985 - M90-71  
-----  
Found - A 1964 DCSO Brass Cap, on a 1½" iron pipe, and the following accessories;  
BTs - 10" Fir snag, 15' tall bears N.31°W., 7.9 ft. No scribing visible. (Orig.)  
      18" Cedar, bears N.48°E., 23.7 ft. (Rec. 24.4 ft.) Closed face. (Orig.) continued next page

TOWNSHIP 27 RANGE 02 POINT IDENTIFIER # 200300

PRIMARY CORNER DESCRIPTION Cor Secs 19, 20, 29, & 30

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

23" Fir, bears S.64°E., 17.8 ft. Closed face. Orig.  
21" Cedar, bears S.62°W., 25.1 ft. (Rec. 26.4 ft.)  
Closed face. (Orig.)  
Down, and uprooted hemlock bears N.22°W., 36.0 ft.  
No scribing visible. (1964)  
New BT - 10" Cedar, bears N.26°W., 32.0 ft. Scribed: T27S R2W  
S19 BT.

BLM dependent resurvey by A. Bert Skeesick & Timothy J Moore,  
Cadastral Surveyors & Robert H Browning, Survey Technician,  
under Group No. 1968, surveyed Aug. 2003/July 2004 - (DCS0  
records Vol. 56 Page(s) 22005-6)

-----

The cor of secs. 19, 20, 29, & 30 remonumented by the Douglas  
County Surveyors Office in 1964, perpetuated by Geisler, in  
1985, monumented with an iron post, 1¼" dia., firmly set,  
projecting 10" above ground, with brass cap (properly) mkd.  
from which the remains of the original bearing trees

- A cedar, 23" dia., bears N.48°E., 24.4 ft., with a healed  
blaze. (Record, N.48°10'E.)
- A cedar, 27" dia., bears S.65½°E., 17.8 ft., with a healed  
blaze. (Record, S.64°10'E.)
- A cedar, 24" dia., bears S.62½°W., 24.9 ft., with scribe  
marks 27S R2W S19 BT on a partially healed double  
blaze. (Record, S.62°10'W., 26.4 ft.)  
and bearing tree mkd. by Geisler
- A cedar, 13" dia., bears N.29°W., 31.8 ft., with scribe  
marks 27S R2W S19 BT visible on a partially healed  
double blaze.