

TOWNSHIP 27 RANGE 02 POINT IDENTIFIER # 200400

PRIMARY CORNER DESCRIPTION Cor Secs 17, 18, 19 & 20

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GL0 resurvey by Morris Wygant, Compass man for Zachariah M. Derrick U.S. Dep. Surveyor, under contract #779, dated Feb. 7, 1908 - (DCSO records Vol. 12 Page(s) 4957)

Set a cedar post, 3 ft. long, 4" sq., 24" in the ground for cor. to secs. 17, 18, 19, & 20, marked T27S S 17 on NE, R2W S 20 on SE, S 19 on SW, S 18 on NW faces, with 3 notches on S & 5 notches on E edges; from which

- A fir, 30" dia., bears N.19°30'E., 51 lks., mkd: T27S R2W S17 BT.
- A cedar, 50" dia., bears S.67°30'E., 63 lks., mkd: T27S R2W S20 BT.
- A fir, 18" dia. bears S.25°W. 23 lks. mkd: T27S R2W S19 BT
- A cedar, 24" dia., bears N.25°30'W., 17 lks., mkd: T27S R2W S18 BT.

Derricks cor. for Secs. 17, 18, 19, & 20, which I now destroy bears N.36°10'W., 730 lks. Note - We have no record of Derrick setting this corner. JC DCSO 9/2008

Douglas Co. Surveyors Office - Milo E. Godfrey, Deputy - Wm. Stoffel - Mike Darby - June 1964 - C.S. File 49/28-20

Found - R.Cedar (now 32" dia.,) N.25½°W., 11.2 ft. shows good scar.
D.Fir (now 32" dia.,) N.19½°E., 33.7 ft. shows very plain axe scar.
I. Cedar (now 52" dia.,) S.67½°E., 41.6 ft. scribing visible in not completely covered scar.
Stump (rotten) rotten fir log S.25°W., 15.2 ft. scribing visible on log.
Partly rotted stake, showing scribing, lying on ground at corner.

Set - Brass cap mkd: COUNTY SURVEYOR OFFICE 1964 T27S R2W

S 18	S 17
S 19	S 20

New BT - 37" D.Fir S.69°W., 24.2 ft. mkd: T27S R2W S19 CS BT

Douglas Co. Surveyors Office - Stephen J. Flause - Debby Stewart - March 30, 1981 - C.S. File 61/19-20

Found - A 1964 DCSO brass cap, properly marked, on a 1" I.P. protrudes 16" from ground & is leaning northeast apparently dislodged by a falling tree. 1964
A cedar stake is lying near the brass cap monument, 3"x4"x18" long shows possible scribe marks. 1964
Orig Fir 30" now 33" DBH D.Fir, bears N.19½°E. 33.7 ft tree has healed dbl blaze no scribing visible

continued next page

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

Orig. Cedar, 50" is now gone, removed by road work.
Orig. Fir, 18" recorded as a rotted stump & log in 1964 is no longer in evidence.
Orig. Cedar 24" now a 32" DBH cedar bears N.25½°W., 11.2 ft. Tree has fully healed double blaze.
37" D.Fir now a 37" DBH D.Fir bears S.69°W., 24.2 ft. Tree has fully healed double blaze.
Set - Location of base of brass cap pipe monument is referenced out (measurement of accessories were checked from this location.) Monument is lowered, plumbed and set firmly at above referenced location. Monument now protrudes 7" from ground. Cedar stake is lain next to monument.
New BTs- 12" DBH Cedar bears S.15½°E., 7.2 ft. and is scribed T27S R2W S20 CS BT on a double blaze.
New DCSO bearing tree tags are placed on all BTs.

BLM dependent resurvey by A. Bert Skeesick & Timothy J Moore, Cadastral Surveyors & Robert H Browning, Survey Technician, under Group No. 1968, surveyed Aug. 2003/July 2004 - (DCSO records Vol. 56 Page(s) 22008-9)

The cor. of secs. 17, 18, 19, & 20, remonumented by the Douglas County Surveyors Office in 1964, and perpetuated by the Douglas County Surveyors Office in 1981, monumented with an iron post, 1¼" dia., firmly set, projecting 5" above ground, with brass cap (properly) mkd. from which the remains of the original bearing trees

- A tin-capped fir stump, 36" dia., bears N.22°E., 33.7 ft., no marks visible. (Record, N.19°30'E.)
- A tin-capped cedar stump, 40" dia., bears N.19°W., 11.2 ft., with a healed blaze. (Record, N.25°0'W.)

and remains of a BT mkd. by the Douglas Co Surveyors Office in 1964

- A tin-capped fir stump, 42" dia., bears S.70¼°W., 24.2 ft., no marks visible.

and remains of a bearing tree mkd. by the Douglas County Surveyors Office in 1981

- A cedar snag, 13" dia., bears S.11¾°E., 7.1 ft., no marks visible.

and new bearing trees

- A fir, 6" dia., bears N.42½°E., 13.8 ft., mkd. T27S R2W S17 BT.
- A fir, 5" dia., bears S.69¾°E., 11.3 ft., mkd. X BT.
- A fir, 6" dia., bears S.19¼°W., 12.8 ft., mkd. T27S R2W S19 BT
- A fir, 6" dia. bears N.57¾°W. 3.5 ft. mkd. T27S R2W S18 BT