

PRIMARY CORNER DESCRIPTION CC Secs. 17 & 18 only, North

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Charles Roberts, US Deputy Surveyor under contract #759 dated Oct. 26, 1904 - (DCSO records Vol. 12 Page(s) 4893)

Set a basalt stone 14x10x7", 10" in the ground for cor. of secs. 7, 8, 17, & 18 mkd with 4 notches on S & 5 notches on E edge, from which

A fir, 30" dia. bears N.47½°E. 50 lks. mkd: T27S R2W S8 BT
A fir, 18" dia. bears S.47°E. 43 lks. mkd: T27S R2W S17 BT
A fir, 22" dia. bears S.30°W. 34 lks. mkd: T27S R2W S18 BT
A fir, 18" dia. bears N.14°W. 122 lks. mkd: T27S R2W S7 BT

GLO resurvey by Morris Wygant, Compass man for Zachariah M. Derrick U.S. Dep. Surveyor, under contract #779, dated Feb. 7, 1908 - (DCSO records Vol. 12 Page(s) 4916)

The cor. of secs. 7, 8, 17, & 18 which is a stone, firmly set, marked & witnessed as described by the surveyor general & which I now change to refer to secs. 7 & 8 only bears South 139 lks. The course of this line from the ¼ sec. cor. is S.87°37'W., and the length is 40.68 chs. (S¼ S8)

GLO resurvey by Morris Wygant, Compass man for Zachariah M. Derrick U.S. Dep. Surveyor, under contract #779, dated Feb. 7, 1908 - (DCSO records Vol. 12 Page(s) 4959-60)

(N.0°04'W.) Intersect South bdy. of Sec. 8, 490 lks., N.87°37'E., of the cor. of secs. 7 & 8

At point of intersection, I set a cedar post, 3 ft. long, 4" sq., 24" in the ground for closing cor. of Secs. 17 & 18, marked CC T27S R2W on S, S17 on E & S 18 on W face, with 1 groove on W & 5 grooves on E face, from which

A fir, 10" dia., bears S.19°30'E., 42 lks., mkd: T27S R2W S17 BT.
A fir, 20" dia., bears S.61°50'W., 12 lks., mkd: T27S R2W S18 BT.

Douglas Co. Surveyors Office - John Powell - Frank Jones - W. Penley - Oct. 1969 - C.S. File 54/40-184

Found - 20" D.Fir, now down, S.62°W. 7.9 ft., opened tree for scribe.

10" D.Fir, now down & rotten, S.19½°E. 27.7 ft.

Set - Brass Cap at C.Cor. mkd: COUNTY SURVEYORS T27S R2W
OFFICE S 8
1969 CC S 18|S 17

continued next page

TOWNSHIP 27 RANGE 02 POINT IDENTIFIER # 200500

PRIMARY CORNER DESCRIPTION CC Secs. 17 & 18 only, North

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

New BTs- 27" Cedar S.2°W. 31.1 ft. mkd: T27S R2W S18 CC CS BT
35" D.Fir S.35°E. 19.2 ft mkd: T27S R2W S17 CS BT CC
10" Cedar N.28°W. 7.3 ft. mkd: T27S R2W S8 CS BT.

Dependent resurvey by Peter A. Peterson & Daniel L. Berry,
Cadastral Surveyors, under Group No. 757, surveyed Aug./Sept.
1971 - (DCSO Records Vol. 35 Page(s) 14594)

The orig. closing cor. of secs. 17 & 18, perpetuated &
recorded by Powell in 1969, monumented with an iron post, 1"
dia. protruding 8" above ground with brass cap (properly) mkd
from which the orig. BTs

A root hole, bears S.19½°E., 42 lks., with a down fir
alongside, 10" dia., no marks visible.

A root hole, bears S.61°50'W., 12 lks., with a down fir
alongside, 20" dia., with illegible scribe marks
visible on opened blaze.

and trees marked by Powell, in 1969

A fir, 35" dia., bears S.35°E., 29 lks. with healed blaze.

A cedar, 27" dia. bears S.2°W., 47 lks, with healed blaze.

A cedar, 10" dia. bears N.28°W., 11 lks. with healed blaze