

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 7 & 8

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Charles Roberts, US Deputy Surveyor under contract #759 dated Oct. 26, 1904 - (DCSO records Vol. 12 Page(s) 4893-4 & Vol. 27 Pg. 11762)

Set a basalt stone 14x10x10", 10" in the ground for ¼ sec. cor. mkd. ¼ on W face, from which
A fir, 24" dia., bears N.88°E., 96 lks., mkd: ¼ S8 BT.
A fir, 20" dia., bears N.20°W., 67 lks., mkd: ¼ S7 BT.

Douglas Co. Surveyors Office - Vernon "Ray" Tracy - Frank Jones - V. Perron - Dec. 1968 - C.S. File 54/40-137

Found - 14x12x10 basalt stone mkd: "¼"
Orig. 24" fir now 26" stump, N.88°E., 63.4 ft., open & find scribe.
Orig. 18" now 28" fir, alive, N.20°W., 44.2 ft. shows good scar.
Set - Brass cap at cor. mkd: COUNTY SURVEYORS T27S R2W
(Reset stone on N side) OFFICE 1968 ¼ S7|S 8
New BTs- 9" D.Fir S.75°E., 15.2 ft. mkd: "¼ S8 CS BT"
14" Pine, S.75°W., 16.9 ft. mkd: "¼ S7 CS BT"
This corner lies on moderate southerly slope.

Dependent resurvey by Peter A. Peterson & Daniel L. Berry, Cadastral Surveyors, under Group No. 757, surveyed Aug./Sept. 1971 - (DCSO Records Vol. 35 Page(s) 14595-6)

The ¼ sec. cor. of secs. 7 & 8, perpetuated & recorded by Tracy in 1968, monumented with an iron post, 1" dia., firmly set, protruding 5" above ground, with brass cap (properly) mkd alongside of which is the orig. basalt stone, 14x10x10" loosely set, 2" in the ground, marked ¼ on W face from which the orig. BTs
A fir stump, 36" dia., bears N.88°E., 96 lks., with scribe marks ¼ S8 BT visible on opened blaze.
A fir, 33" dia., bears N.20°W., 67 lks., with healed blaze and trees marked by Tracy, in 1968
A fir, 10" dia., bears S.75°E., 23 lks., with healed double blaze.
A pine, 17" dia., bears S.75°W., 26 lks., with healed double blaze.

Fd. & used on BLM Dependent resurvey by Wayne Rogers, Cadastral Surveyor, under Group #983, surveyed May/Aug 1979 - (DCSO records Vol. 44 Page(s) 16931-2)

continued next page

TOWNSHIP 27 RANGE 02 POINT IDENTIFIER # 200540

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 7 & 8

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Bruce Shaner - Feb. 17, 1994 - C.S. 63/154-2

Found - County Surveyors Office

T27S
¼ S7|S8 R2W
1968

2½ Brass cap on a 1" iron pipe, from which a:
36" D. Fir BT stump, scribes visible, bears N88°E.,
63.4 ft.

38" D. Fir BT, face overgrown, bears N.20°W. 44.2 ft
10" D. Fir BT, now a windfall, bears S.75°E. 15.2 ft
20" Pine BT, now down, bears S.75°W., 17.2 ft. (rec.
16.9 ft.)

Basalt stone, probable original corner, no mark
visible (stone is 14"x12"x10") lies adjacent
brass cap.

New - 44" D. Fir BT, I scribed "¼ S7 BT" bears S.14°W.,
76.6 ft.

10" D. Fir BT, I scribed "¼ S8 BT" bears N.70°E.,
31.6 ft.

14" D. Fir BT, I scribed "¼ S8 BT" bears S.83°E.,
25.0 ft.

6 ft. steel post, I set, bears North, 1.0 ft.

Area was logged this year in sec. 7 to the West. Blm road
ends N.60°W., 300 ft. from corner

Fd. Ok by M Heimburger, M157-50