

PRIMARY CORNER DESCRIPTION Cor. secs. 5, 6, 7, & 8

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO Survey by Samuel C. Flint, Under Contract #459, dated Aug. 3, 1882 (DCSO Records Vol. 12 Page(s) 4882)

-----

Set Laurel post, 4 ft. long, 4" sq., 24" in the ground for cor. to secs. 5, 6, 7, & 8, marked T27S S 5 on NE, R2W S 8 on SE, S 7 on SW, S 6 on NW faces, with 5 notches on S & East edges; from which

    A fir, 48" dia. bears S.35°W., 35 lks. mkd: T27S R2W S7 BT

    A fir, 45" dia. bears S.40°E., 65 lks. mkd: T27S R2W S8 BT

    A fir, 12" dia. bears N.45°E., 72 lks. mkd: T27S R2W S5 BT

No tree within limits NW; raised stone mound around post. This cor. is on the southern slope of a very high mountain.

GLO survey by Charles Roberts, US Deputy Surveyor under contract #759 dated Oct. 26, 1904 - (DCSO records Vol. 12 Page(s) 4899-4900)

-----

I reestablish the cor. of secs. 5, 6, 7, & 8, which is a stone mound with remains of charred post in center, witnessed as described by the Surveyor General. The BTs having been killed by fire & marks on same nearly obliterated, I destroy all traces of old cor. & mark a cross (X) at exact point of old cor. on a point of bed rock 24x24x48" above the ground, notches impracticable, I raise a mound of stone, 2 ft. base, 1½ ft. high W of cor., from which

    A fir, 16" dia. bears N.84°E., 141 lks mkd: T27S R2W S5 BT

    A fir, 48" dia. bears S.65°E., 137 lks mkd: T27S R2W S8 BT

    A fir, 30" dia., bears S.23½°W., 154 lks., mkd: T27S R2W S7 BT.

    A fir, 8" dia. bears N.31°W., 107 lks. mkd: T27S R2W S6 BT

Douglas Co. Surveyors Office - Vernon "Ray" Tracy - Frank Jones - V. Perron - Dec. 1968 - C.S. File 54/40-141

-----

Found - 3" + on rock outcrop 6 ft long, 2 ft. high & 1905 BTs as follows:

    16" now 24" Fir, alive, N.84°E., 93.1 ft. open & find scribe.

    48" now 54" Fir, alive, S.65°E., 90.4 ft. shows good scar.

    30" now 38" Fir, alive, S.23½°W., 101.6 ft., scribe visible on previously opened blaze.

    8" now 24" fir alive, N.31°W., 70.6 ft., opened, probable scribe marks visible.

Set Brass cap 1' West of corner point mkd: T27S R2W

COUNTY SURVEYORS	S 6   S 5
OFFICE 1968	S 7   S 8

continued next page

PRIMARY CORNER DESCRIPTION Cor. secs. 5, 6, 7, & 8

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

<p>New BTs- 14" D.Fir S.78°W., 9.4 ft. mkd: T27S R2W S7 CS BT. 12" D.Fir N.60°W., 11.3 ft. mkd: T27S R2W S6 CS BT. 10" D.Fir N.50½°E., 7.7 ft. mkd: T27S R2W S5 CS BT. 14" D.Fir S.2°E., 23.7 ft. mkd: T27S R2W S8 CS BT. <u>(Bear. &amp; dist. from true corner, not brass cap - lines well blazed E &amp; S)</u></p>
<p>FD. &amp; used on Dependent resurvey by Peter A. Peterson &amp; Daniel L. Berry, Cadastral Surveyors, under Group No. 757, surveyed Aug/Sept 1971 - (DCSO Records Vol. 35 Pages 14596-7)</p>
<p>Fd. &amp; used on BLM Dependent resurvey by Wayne Rogers, Cadastral Surveyor, under Group #983, surveyed May/Aug 1979 - (DCSO records Vol. 44 Page(s) 16918-9)</p>
<p>BLM Dependent Resurvey by Kenneth W. Saveland, Cadastral Surveyor, under Group No. 2500, Surveyed Aug./Nov. 2011 - (DCSO records BLM Plat T27-2W 2012-1 &amp; Vol. 58 Pages 22947-8)</p> <p>-----</p> <p>The cor. of secs. 5, 6, 7, &amp; 8, monumented with a brass tablet, cemented in a rock outcropping, 2 ft. x 4 ft., 2 ft. high, with brass cap (properly) mkd from which the remains of BTs mkd. by Roberts</p> <ul style="list-style-type: none"><li>A fir snag, 35" dia., bears N.84°E., 127.3 ft. with a previously chopped open &amp; now healed blaze (Rec 93.1 ft)</li><li>A sawed fir stump, 54" dia., S.65°E., 90.4 ft. with a healed blaze.</li><li>A fir, 50" dia., bears S.23½°W., 97.3 ft. with a healed blaze. (Rec. 101.6 ft.)</li><li>A fir, 35" dia., bears N.31°W., 73.9 ft. with a healed blaze. (Rec. 70.6 ft.)</li></ul> <p>and BTs mkd by the DCSO in 1968</p> <ul style="list-style-type: none"><li>A fir, 13" dia., bears N.50°E., 7.9 ft. with a healed double blaze.</li><li>A fir, 19" dia., bears S.2°E., 23.8 ft. with a healed double blaze.</li><li>A fir, 18" dia., bears S.78°W., 9.2 ft. with a healed double blaze.</li><li>A fir, 14" dia., bears N.60°W., 11.2 ft. with a healed double blaze.</li></ul> <p>and RM set by the DCSO in 1968</p> <ul style="list-style-type: none"><li>An iron post 1¼" dia., firmly set, projecting 8" above a collar of stone, bears N.80°51'42"W., 1.19 ft. with brass cap mkd. COUNTY SURVEYORS OFFICE T27S R2W S5 S6 S7 S8 1968 (Rec. West, 0.99 ft.)</li></ul> <p>(NAD 1983 (CORRS 96))</p> <p>Latitude 43°14'34.314"N Longitude 122°58'18.228"W</p>