TOWNSHIP 27 RANGE 02 POINT IDENTIFIER # 236500

PRIMARY CORNER DESCRIPTION S 1/4 Cor. Sec. 8 only

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Charles Roberts, US Deputy Surveyor under contract #759 dated Oct. 26, 1904 - (DCSO records Vol. 12 Page(s) 4892-3)

Set a basalt stone 24x18x10", 16" in the ground for ¼ sec. cor. mkd. ¼ on N face, from which
A fir, 18" dia., bears N.19½°E., 99 lks., mkd: ¼ S8 BT.
A fir, 24" dia., bears S.35½°W., 79 lks., mkd: ¼ S17 BT.
From this corner John Gardener's house bears N.2°20'E.
John W. Greenman's house bears N.9°30'W.
John E. Greenman's house bears N.24°35'W.

GLO resurvey by Morris Wygant, Compass man for Zachariah M. Derrick U.S. Dep. Surveyor, under contract #779, dated Feb. 7, 1908 - (DCSO records Vol. 12 Page(s) 4915-6)

The ¼ sec. cor. which is a stone, firmly set, marked & witnessed as described by the surveyor general & which I now change to refer to sec. 8 only.

Douglas Co. Surveyors Office - John Powell - Frank Jones - W. Penley - Oct. 1969 - C.S. File 54/40-185

Found - 24x13x10 Stone, firmly set, mkd: "¼" on north face.
18" D.Fir, now 28, N.19½°E. 65.3 ft., tree opened & burnt.
24" now 31" D.Fir, S.35½°W. 52.1 ft. shows good scar
Set - Brass Cap at Cor. Mkd: COUNTY SURVEYORS OFFICE 1969 T27S R2W ¼ S 8
New BTs- 6" D.Fir N.6°W., 42.1 ft. mkd: "¼ S8 CS BT".
8" Pine N.44°E., 48.5 ft. mkd: "¼ S8 CS BT".

Dependent resurvey by Peter A. Peterson & Daniel L. Berry, Cadastral Surveyors, under Group No. 757, surveyed Aug./Sept. 1971 - (DCSO Records Vol. 35 Page(s) 14593-4)

The ¼ sec. cor. of sec. 8 only, perpetuated by Powell in 1969, monumented with an iron post, 1" dia., firmly set, protruding 18" above ground & in a mound of stone, 3 ft. base, to top, with brass cap (properly) marked alongside of which is the orig. basalt stone, 24x18x10" mkd ¼ on N face, from which the orig. BTs
A fir, 30" dia., bears N.19½°E., 99 lks., with burned & opened blaze.
A fir, 41" dia., bears S.35½°W., 79 lks., with healed blaze.
and trees mkd by Powell in 1969
continued next page

TOWNSHIP 27 RANGE 02 POINT IDENTIFIER # 236500

PRIMARY CORNER DESCRIPTION S 1/4 Cor. Sec. 8 only

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

A pine, 8" dia., N.44°E., 74 lks., with scribe marks ¼ S8 BT visible on partially healed blaze.
A fir, 8" dia., N.7°W., 6 lks., with healed double blaze.

Fd. Ok by D. Edwards, 9/1998 - M130-47