

PRIMARY CORNER DESCRIPTION A P on So. bdy. Sec. 32

Alias \_\_\_\_\_ Description \_\_\_\_\_  
 Alias \_\_\_\_\_ Description \_\_\_\_\_  
 Alias \_\_\_\_\_ Description \_\_\_\_\_  
 Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by S.C. Flint, Contract #459, dated August 3, 1882  
 - (DCSO records Vol. 12 Page(s) 4864)

-----  
 Set Cedar post 3 ft. long, 3" sq., 24" in the ground for  
 standard ¼ sec. cor. marked S C ¼ S on N. face, from which  
     A Cedar 12" dia., bears S.62°E., 8 lks. dist. mkd. S C ¼  
     S BT.  
     A Hemlock 8" dia., bears N.12°W., 20 lks. dist. mkd. S C  
     ¼ S BT.

GLO Resurvey by Morris Wygant, Compassman for Zachariah  
 Derrick, U.S. Deputy Surveyor, Under Contract #779, dated  
 Feb. 7, 1908 - (DCSO records Vol. 12 Page(s) 4906)

-----  
 The standard ¼ sec. cor., which is a post, firmly set, mkd.  
 and witnessed as described by the surveyor general, bears S.  
 30 lks. dist. I now change this cor. to an Angle Point, as  
 follows:  
 Cut out all marks and remark AP on N. face; then cut out all  
 BTs and remark AP BT.

Douglas County Surveyors Office - Vernon "Ray" Tracy and crew  
 June 12, 1969 - C.S. File 54/40-171

-----  
 Found - Unrecorded 3/4" I.P. at Corner point. 3/4" I.P. in  
         good condition.  
         Orig. 12" now 20" Cedar, S.62°E., 5.3 ft., open and  
         found scribe marks.  
         Orig. 8" now 12" Hemlock, N.12°W., 13.2 ft., down  
         and decaying. Prev. opened blaze, rotted away.  
 Did Not Set Brass Cap.  
 New BTs- 22" Cedar S.18°E., 6.3 ft. mkd. AP CS BT.  
         18" Cedar N.35°E., 23.9 ft. mkd. AP CS BT.  
 Cor. lies on moderate southerly slope in old growth timber.

Survey by Romano E. Ware and Ronald Quimby - For: U.S.  
 Forest Service - July 1980 - M 79-49

-----  
 Found - Unrecorded 3/4" Iron pipe.  
         24" Cedar stump, S.18°E., 6.3 ft. visible scribe.  
         20" Cedar stump, S.62°E., 5.3 ft., good face.  
         20" Cedar N.35°E., 23.9 ft. visible scribe.  
 Set 2½" Iron pipe with brass cap mkd. "T27S R2W AP S32 S5  
 T28S RLS 1654 1980", over top of 3/4" I.P.  
 New BT - 22" Cedar, South 41.7 ft. mkd. "AP S5 BT". Brass  
         washer set in BT face.  
 Set post and sign 4.0 ft. North.

cont.

TOWNSHIP 27 RANGE 02 POINT IDENTIFIER # 239100

PRIMARY CORNER DESCRIPTION A P on So. bdy. Sec. 32

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

BLM dependent resurvey by A. Bert Skeesick & Timothy J Moore, Cadastral Surveyors & Robert H Browning, Survey Technician, under Group No. 1968, surveyed Aug. 2003/July 2004 - (DCSO records Vol. 56 Page(s) 21982-3)

-----

Angle Point for secs. 32 and 5, on the S. bdy. of the Tp., originally established as the standard  $\frac{1}{4}$  sec. cor. of sec. 32, in 1882, perpetuated by the Douglas County Surveyors Office in 1969 and remonumented by Ware and Quimby in 1980, monumented with an iron post, 2" dia., firmly set, projecting 5" above ground, with brass cap (properly) mkd. from which the remains of the original bearing trees

A decayed cedar stump, 18" dia., bears S.  $56\frac{3}{4}^{\circ}$ E., 6.0 ft., with no scribe marks visible on chopped out blaze. (Record, S.  $62^{\circ}$ E., 5.3 ft.)

and remains of BTs mkd by the Douglas County Surveyors Office

A roothole bears N.  $30^{\circ}$ E., 21.4 ft., with fallen cedar trunk, 19" dia., lying alongside, with scribe marks BT visible on a partially healed blaze.

A decayed cedar stump, 21" dia. bears S.  $18^{\circ}$ E. 6.4 ft. with scribe marks S BT visible on a partially healed blaze. and remains of bearing trees mkd. Ware and Quimby

A cedar stump, 21" dia., bears S.  $1\frac{1}{4}^{\circ}$ W., 41.2 ft., with scribe marks BT visible on a partially healed blaze. and new bearing tree

A cedar, 19" dia., bears N.  $21\frac{1}{2}^{\circ}$ E., 29.0 ft., mkd. X BT.