

TOWNSHIP 27 RANGE 02 POINT IDENTIFIER # 240140

PRIMARY CORNER DESCRIPTION Center 1/4 Cor. Sec. 32

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Romanso E. Ware & Ronald Quimby - For: US Forest Service -
July 1980 - M79-49

Set - 2½" Iron pipe with brass cap marked: T27S R2W C¼ S32
RLS 1654 1980.

New BTs- 10" Fir, S.41°E., 15.1 ft "C ¼ S32 BT"
8" Hemlock, S.44°W., 34.4 ft. "C ¼ S32 BT".

Set post & sign 3.0 ft. North. Brass washer marked RLS 1654
Set in BT faces.

BLM dependent resurvey by A. Bert Skeesick & Timothy J Moore,
Cadastral Surveyors & Robert H Browning, Survey Technician,
under Group No. 1968, surveyed Aug. 2003/July 2004 - (DCSO
records Vol. 56 Page(s) 22024-5)

The center ¼ sec. cor. of sec. 32, established by Ware and
Quimby in 1980, and is accepted as the cor., monumented with
an iron post, 2½" dia., firmly set, projecting 4" above
ground, with brass cap (properly) mkd.

from which bearing trees mkd. by Ware and Quimby

A fir, 19" dia., bears S.42½°E., 34.6 ft., with a healed
double blaze.

A hemlock, 12" dia., bears S.42¼°W., 15.0 ft., with scribe
marks C ¼ S32 visible on a partially healed double
blaze.