

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 20 & 29

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO resurvey by Morris Wygant, Compass man for Zachariah M. Derrick U.S. Dep. Surveyor, under contract #779, dated Feb. 7, 1908 - (DCSO records Vol. 12 Page(s) 4954-5)

West, on true line bet. Secs. 20 & 29, 40.12 chs.
Set a cedar post, 3 ft. long, 4" sq., 24" in the ground, for 1/4 sec. cor., marked 1/4 S20 on N & 29 on S face; from which
 A hemlock, 24" dia. bears S.33°30'W. 16 lks. mkd: 1/4 S29 BT
 A cedar, 12" dia., bears N.21°E., 39 lks., mkd: 1/4 S20 BT.
41.90 chs
Derricks 1/4 sec. cor. which I now destroy, bears N 500 lks.
Note - We have no record of Derrick setting this corner.
 JC DCSO 9/2008

Douglas Co. Surveyors Office - Vernon "Ray" Tracy - Dec. 1968 & March 23, 1969 - C.S. File 54/40

Found?? Dec. 1968 C.S. File 54/40-145
We find 2 old hub lines & no trace of OBTs on either.
Numerous trees have been chopped open.
March 1969 C.S. File 54/40-166
Found OBT 8?" now 16" hemlock bears approx. S.35°E., ?? dist. scribed "1/4 S29 BT" visible on open blaze. This corner lies approx. 100 ft. E of creek course NE. I believe it to be Derricks BT - The cor. was reported destroyed by Wygant in subsequent survey - we have no record of a hemlock this size or bearing. A hub line approx. 300 ft. S would fit Wygant's calls on creeks. WE DO NOT FIND WYGANT'S BTS.

Ronald G. Geisler, Champion International - June/Aug 1985 - M90-71

Set - A 2 1/2" alum. cap on a 2 1/2"x30" alum., flared pipe; mkd. PLS 1988
BTs - 4" Fir, bears N.22°W., 16.4 ft. Scribed X BT.
 4" Fir, bears S.34°W., 18.8 ft. Scribed X BT.

BLM dependent resurvey by A. Bert Skeesick & Timothy J Moore, Cadastral Surveyors & Robert H Browning, Survey Technician, under Group No. 1968, surveyed Aug. 2003/July 2004 - (DCSO records Vol. 56 Page(s) 22004)

The 1/4 sec. cor. of secs. 20 & 29, determined at record bearing and from the remains of an original BT
 A cedar stump, 27" dia., bears N.21°E., 25.7 ft., with scribe marks BT visible on fragmentary remains of the reverse scribe of a healed blaze.
At the corner point continued next page

TOWNSHIP 27 RANGE 02 POINT IDENTIFIER # 240300

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 20 & 29

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Set a stainless steel post, 28" long, 2½" dia., 23" in the ground, with brass cap mkd. T27S R2W

S 20

¼

S 29

2004

from which new bearing trees

A fir, 15" dia., bears N.27°E., 3.9 ft., mkd. ¼ S20 BT.

A fir, 13" dia., bears S.69¼°E., 11.2 ft., mkd. ¼ S29 BT.

Deposit a magnet in a white plastic case at the base of the stainless steel post.

From this corner, a point established at proportionate (overlooking existing original evidence) as the ¼ sec. cor. of secs. 20 and 29 by Geisler, in 1985, and is not accepted as the cor. and not utilized in the course of this survey, bears N.9°27'28"W., 18.52 ft., monumented with an aluminum post, 2" dia., firmly set, projecting 4" above ground, with aluminum cap mkd. CHAMPION INTL CORP T27S R2W S20 ¼ S29 1985 PLS 1988.

from which bearing trees mkd. by Geisler

A fir, 12" dia., bears S.33¾°W., 18.9 ft., with a healed blaze.

A fir, 12" dia., bears N.22¾°W., 16.3 ft., with a healed blaze.