

PRIMARY CORNER DESCRIPTION South 1/4 Cor. Sec. 5 only

Alias	Description

<p>GLO Survey by Samuel C. Flint, Under Contract #459, dated Aug. 3, 1882 (DCSO Records Vol. 12 Page(s) 4882)</p> <p>-----</p> <p>Set Maple post, 3 ft. long, 3" sq., 24" in the ground, for ¼ sec. cor., marked ¼ S on N &amp; S faces; from which</p> <p>    A maple, 8" dia., bears S.48°W., 27 lks., mkd: ¼ S BT.</p> <p>    A fir, 40" dia., bears N.85°W., 22 lks., mkd: ¼ S BT.</p>
<p>Fd. on GLO survey by Charles Roberts, US Deputy Surveyor under contract #759 dated Oct. 26, 1904 - (DCSO records Vol. 12 Page(s) 4900)</p>
<p>Dependent resurvey by Peter A. Peterson &amp; Daniel L. Berry, Cadastral Surveyors, under Group No. 757, surveyed Aug./Sept. 1971 - (DCSO Records Vol. 35 Page(s) 14597)</p> <p>-----</p> <p>Point for the ¼ sec. cor. of sec. 5 only, determined by the method of irregular boundaries; there is no remaining evidence of the orig. corner.</p> <p>Set an iron post, 28 long, 2½" dia., 22" in the ground with brass cap marked:</p> <p style="text-align: center;">    <u>¼ S 5</u>     T27S R2W     1971</p> <p>from which</p> <p>    A fir, 55" dia., bears N.81°W., 89 lks., mkd: ¼ S5 BT.</p> <p>No other suitable trees available within limits.</p>
<p>BLM Dependent Resurvey by Kenneth W. Saveland, Cadastral Surveyor, under Group No. 2500, Surveyed Aug./Nov. 2011 - (DCSO records BLM Plat T27-2W 2012-1 &amp; Vol. 58 Pages 22947-8)</p> <p>-----</p> <p>The ¼ sec. cor. of sec. 5 only, monumented with an iron post, 2½" dia., firmly set, projecting 4" above ground, with brass cap (properly) mkd.</p> <p>from which the remains of a BT mkd by Peterson &amp; Berry</p> <p>    A fir snag, 44" dia., bears N.78½°W., 55.3 ft. with fragmentary scribe marks visible on a partially healed, decayed blaze. (Rec. N.81°W., 58.7 ft.)</p> <p>and new BTs</p> <p>    A madrone, 12" dia., bears N.83½°W., 30.4 ft., mkd: ¼ S5 BT in the bark.</p> <p>    A fir, 17" dia., bears N.19½°W., 18.4 ft., mkd: ¼ S5 BT.</p>