

PRIMARY CORNER DESCRIPTION North 1/4 Sec. 8 only

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

GLO Survey by Samuel C. Flint, Under Contract #459, dated Aug. 3, 1882 (DCSO Records Vol. 12 Page(s) 4882)

-----

Set Maple post, 3 ft. long, 3" sq., 24" in the ground, for ¼ sec. cor., marked ¼ S on N & S faces; from which  
 A maple, 8" dia., bears S.48°W., 27 lks., mkd: ¼ S BT.  
 A fir, 40" dia., bears N.85°W., 22 lks., mkd: ¼ S BT.

Fd. on GLO survey by Charles Roberts, US Deputy Surveyor under contract #759 dated Oct. 26, 1904 - (DCSO records Vol. 12 Page(s) 4900)

Dependent resurvey by Peter A. Peterson & Daniel L. Berry, Cadastral Surveyors, under Group No. 757, surveyed Aug./Sept. 1971 - (DCSO Records Vol. 35 Page(s) 14598)

-----

Point for the ¼ sec. cor. of sec. 8 only, at midpoint longitudinally on the N bdy. of sec. 8.  
 Set an iron post, 28" long, 2½" dia., 20" in the ground, in a mound of stone, 2 ft base, to top, with brass cap marked:

$\frac{1}{4}$  S 8  
 T27S R2W  
 1971

from which  
 A maple, 3" dia., bears S.33°E., 17 lks., mkd: X BT.  
 No other suitable tree available within limits.

Ronald Geisler, LS 1988 - For: Champion International - Aug/Oct 1984 - M90-60

-----

Found - 1971 BLM brass cap/iron pipe.  
 4" double trunked maple bears S.33°E., 11.6 ft. (rec. 11.2 ft.) No scribing fd - rescribed: X BT  
 New BT - 6" maple bears S.16°E., 38.3 ft. scribed ¼ S8 BT.

Fd. Ok 9/1998 - D.Edwards, M130-47

BLM Dependent Resurvey by Kenneth W. Saveland, Cadastral Surveyor, under Group No. 2500, Surveyed Aug./Nov. 2011 - (DCSO records BLM Plat T27-2W 2012-1 & Vol. 58 Pages 22947-8)

-----

The ¼ sec. cor. of sec. 8 only, perpetuated by Geisler in 1984, monumented with an iron post, 2½" dia., firmly set, projecting 10" above ground, with brass cap (properly) mkd. from which a BT mkd by Peterson & Berry  
 A forked maple, 9" dia., bears S.33°E., 11.2 ft. with a healed double blaze. continued next page

TOWNSHIP 27 RANGE 02 POINT IDENTIFIER # 241600

PRIMARY CORNER DESCRIPTION North 1/4 Sec. 8 only

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

and the remains of a BT mkd. Geisler  
A sawed maple stump, 11" dia., bears S.16°E., 38.6 ft.  
with a healed blaze.  
and a new BT  
A fir, 4" dia., bears S.68¾°E., 7.7 ft., mkd: X BT.  
Add a collar of stone around the iron post.