

TOWNSHIP 27 RANGE 02 POINT IDENTIFIER # 276500

PRIMARY CORNER DESCRIPTION CC Secs. 8, 9, & 17

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Charles Roberts, US Deputy Surveyor under contract #759 dated Oct. 26, 1904 - (DCSO records Vol. 12 Page(s) 4891A)

Set a basalt stone 15x7x6", 11" in the ground for cor. of secs. 8, 9, 16, & 17 mkd with 4 notches on S & 4 notches on E edge, from which
A fir, 40" dia. bears N.81°E., 69 lks. mkd: T27S R2W S9 BT
A madrone, 14" dia., bears S.31°E., 47 lks., mkd: T27S R2W S16 BT.
A fir, 36" dia. bears S.56°W. 15 lks. mkd: T27S R2W S17 BT
A fir, 40" dia. bears N.19°W., 69 lks. mkd: T27S R2W S8 BT

GLO resurvey by Morris Wygant, Compass man for Zachariah M. Derrick U.S. Dep. Surveyor, under contract #779, dated Feb. 7, 1908 - (DCSO records Vol. 12 Page(s) 4915)

The cor. of secs. 8, 9, 16, & 17 which is a stone, firmly set, marked & witnessed as described by the surveyor general & which I now change to refer to secs. 8 & 9 only.

Douglas Co. Surveyors Office - Vernon "Ray" Tracy - 5/1969 - C.S. File 54/40-165

Bluffs & numerous slides in this area. No lines or BTs

Dependent resurvey by Peter A. Peterson & Daniel L. Berry, Cadastral Surveyors, under Group No. 757, surveyed Aug./Sept. 1971 - (DCSO Records Vol. 35 Page(s) 14591)

The cor. of secs. 8 & 9 only, on the N. Bdy of sec. 17, monumented with the orig. basalt stone, 15x7x6", firmly set 10" in the ground, mkd with 4 notches on S & 4 notches on E edge, from which the orig. BTs
A fir, 44" dia., bears N.81°E., 69 lks., with healed blaze
A madrone, 20" dia., bears S.31°E., 47 lks., with healed blaze.
A fir, 42" dia., bears S.56°W., 15 lks., with healed blaze
A fir, 43" dia., bears N.19°W., 69 lks., with healed blaze
At the corner point
Set an iron post, 28" long, 2½" dia., 23" in the ground, with brass cap marked:
 S 8 | S 9
 S 17
 1971
Deposit orig. stone alongside the iron post.