

PRIMARY CORNER DESCRIPTION C C for Secs. 4 & 5, T28-2

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by William N. Gibb, Deputy Surveyor, under Contract #783, dated Dec. 3, 1908 - (DCSO records Vol. 13 Page(s) 5462)

-----  
Intersect 6th standard parallel, 150 lks. W. of cor. secs. 32 and 33.  
Set Fir post 3 ft. long, 4" sq., 24" in the ground for closing cor. secs. 4 and 5 marked CC T28S R2W on S.; S4 on E.; and S5 on W. face, with 4 grooves on E. and 2 grooves on W. face, from which  
    A Chinquapin 10" dia., bears S.17°E., 21 lks. dist. mkd. T28S R2W S4 BT.  
    A Laurel 12" dia., bears S.68°W., 17 lks. dist. mkd. T28S R2W S5 BT.

Douglas County Surveyors Office - Vernon "Ray" Tracy and crew June 12, 1969 - C.S. File 54/40-172

-----  
Found - Unrecorded 3/4" Iron pipe set from one O.B.T.  
    Orig. 12" now 20" Laurel S.68°W., 11.2 ft. alive, we open and find S R 2 scribe and reverse.  
    No trace O.B.T. to SE.  
Do Not Set Brass Cap.  
New BTs- 18" Chinquapin S.20°W., 31.5 ft. mkd. T28S R2W S5 CC CS BT.  
    30" D.Fir S.62°E., 34.7 ft. mkd T28S R2W S4 CC CS BT  
    20" Laurel S.68°W., 11.2 ft Remark OBT "CC S5 CS BT"  
(The AP Cor. (old SC of 32 & 33, T27-2) bears East 96.3 ft.)

Survey by Romanso E. Ware and Ronald A. Quimby - For: U.S. Forest Service - July 1980 - M 79-49

-----  
Found - 18" Madrona, S.68°W., 11.2 ft. visible scribes.  
    32" D.Fir, S.62°E., 34.7 ft., good scar.  
Set 2½" I.P. with brass cap over top of 3/4" I.P., mkd. "T28S R2W S5 S4 CC RLS 1654 1980".  
Rescribed- 32" D.Fir "CC T28S R2W S4 BT". Brass washer mkd. "RLS 1654" set in BT face.  
Set post and sign 3.0 ft. West.

BLM dependent resurvey by A. Bert Skeesick & Timothy J Moore, Cadastral Surveyors & Robert H Browning, Survey Technician, under Group No. 1968, surveyed Aug. 2003/July 2004 - (DCSO records Vol. 56 Page(s) 21981)

-----  
The orig. closing cor. of secs. 4 & 5, T28S R2W bears south, 3.53 ft.; perpetuated by the Douglas Co. Surveyors Office in 1969 & remonumented by Ware & Quimby in 1980, cont. next pg.

TOWNSHIP 27 RANGE 02 POINT IDENTIFIER # 277100

PRIMARY CORNER DESCRIPTION C C for Secs. 4 & 5, T28-2

Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____

monumented with an iron post, 2" dia., firmly set, projecting 10 ins. above ground, with brass cap (properly) mkd. from which the remaining original bearing tree

A laurel, 18" dia., bears S.68°W., 11.2 ft., with fragmentary scribe marks visible on a partially healed blaze. (Rescribed by the Douglas Co. Surveyors Office.) and a BT mkd. by the Douglas County Surveyors Office

A fir, 34" dia. bears S.63°E., 35.1 ft with a healed blaze