

TOWNSHIP 27 RANGE 02 POINT IDENTIFIER # 300140

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 32 & 33

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

<p>GLO resurvey by Morris Wygant, Compass man for Zachariah M. Derrick U.S. Dep. Surveyor, under contract #779, dated Feb. 7, 1908 - (DCSO records Vol. 12 Page(s) 4945-6)</p> <p>-----</p> <p>Set a Chinquapin post, 3 ft. long, 4" sq., 24" in the ground, for 1/4 sec. cor., mkd 1/4 S32 on W & S33 on E faces; from which A fir, 36" dia., bears N.53°40'E., 36 lks., mkd: 1/4 S33 BT. A fir, 36" dia., bears N.30°10'W., 8 lks., mkd: 1/4 S32 BT.</p>
<p>Thomas E. Shrum, Jr. - For: US Plywood Corp. - Nov. 1962 - C.S. File 51/254-4 SEE SHRUM 1969 REPORT C.S. 51/254-26</p> <p>-----</p> <p>Found - 1 1/2" Iron pipe 38" D. Fir stump, N.53 1/2°W., 23.8 ft. (good condition) Set - 2 1/2" Alum. cap 11" Cedar S.48°E., 20.3 ft. mkd: 1/4 S33 BT.</p>
<p>Douglas Co. Surveyors Office - Vernon "Ray" Tracy - Frank Jones - V. Perron - Dec. 1968 - C.S. File 54/40-155</p> <p>-----</p> <p>Found - Orig. 36" now 40" fir, sawed stump, N.53 2/3°E., 23.8 ft., we open & find "1/4 S33" scribe & reverse. 36" now 40" Fir sawed stump N.30°W., 5.3 ft. prev. opened "1/4 S32" shows scribe.</p> <p>Set - 1" IP & Brass cap at cor mkd: County Surveyors T27S R2W Office 1968 1/4 S33 S32</p> <p>Set 6' steel fence post alongside brass cap.</p> <p>New BTs- 10" Hemlock N.80°E., 14.6 ft. mkd: 1/4 S33 CS BT 12" Hemlock S.45 1/2°E., 23.5 ft. mkd: 1/4 S33 CS BT No trees available west of line in Sec. 32</p> <p>Note - The 1/4 cor. recorded in 1962 (Shrum) bears S.63°E., 20.3 ft., a 1 1/2" IP with 1" steel pipe & 2 1/2" alum. US Plywood cap with BT apparently set from wrong bearing & dist. from OBT to NW.</p>
<p>Thomas E. Shrum, Jr. - For: US Plywood Corp. - Jan. 1969 - C.S. File 51/254</p> <p>-----</p> <p>Destroyed erroneous corner set by me in Dec. 1962</p>
<p>Romanso E. Ware - For: US Forest Service - June 1980 - M79-49</p> <p>-----</p> <p>Found - 1968 county brass cap. 42" fir stump N.58°E., 23.0' vis. scribe 14" hemlock N.78°E., 14.6' vis. scribe 14" hemlock S.45°E., 23.5' vis. scribe 42" fir stump N.18°W., 6.0' vis. scribe</p> <p>Set - Post & sign 5.0' north <u>cont.</u></p>

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 32 & 33

Alias	Description
Alias	Description
Alias	Description
Alias	Description

Kristian DeGroot, PLS #1941- June 1998 - C.S. File 65/20-31

Found - 1 1/4" (O.D.) IP, firmly set, projecting 12" above a 36" dia. mound of stone w/2 1/2" brass cap properly stamped, from which the OBTs
42" sawed fir stump bears N.54°E., 23.8 ft. w/scribe marks "1/4 S33 BT" visible. (Rec N.53°40'E. 36 lks)
42" sawed fir stump bears N.30°W. 5.3 ft. w/scribe marks "1/4 S 32" visible (Rec. N.30°10'W., 8 lks)
21" Hemlock bears N.81°E., 13.9 ft. w/ healed blaze. (Rec. N.80°E., 14.6 ft.)
16" Hemlock snag bears S.44°E., 23.5 ft. w/scribe marks "1/4 S33 CS BT" visible. (Rec.S45°30'E)
New BT - 13" Hemlock bears S.38°W., 21.2 feet scribed "1/4 S32 BT" on a double blaze with a brass washer stamped "PLS 1941" nailed into lower blaze.
I paint a 6" red band and BT faces red and nail USFS "BEARING TREE" and "LAND SURVEY MONUMENT" signs to all bearing trees.

BLM dependent resurvey by A. Bert Skeesick & Timothy J Moore, Cadastral Surveyors & Robert H Browning, Survey Technician, under Group No. 1968, surveyed Aug. 2003/July 2004 - (DCS0 records Vol. 56 Page(s) 21990-1)

The 1/4 sec. cor. of secs. 32 and 33, remonumented by the Douglas County Surveyors Office in 1968, and perpetuated by DeGroot, in 1998, monumented with an iron post, 1 1/4" dia., firmly set, projecting 4" above ground, in a mound of stone, 2 ft. base, to top, with brass cap (properly) mkd. from which the remains of the original bearing trees
A sawed fir stump, 51" dia., bears N.53 1/2°E., 23.8 ft., with scribe marks 1/4 S3 BT visible on an opened blaze. (Record, N.53°40'E.)
A sawed fir stump, 40" dia., bears N.25 3/4°W., 5.3 ft., with scribe marks 1/4 S32 visible on an opened blaze. (Record, N.30°10'W.)
and remains of BTs mkd. by the Douglas Co Surveyors Office
A hemlock, 22" dia., bears N.79°E., 13.4 ft., with a healed blaze.
A hemlock snag, 15" dia., bears S.45°E., 22.4 ft., with scribe marks 1/4 S33 CS BT visible on a partially healed blaze.
and a bearing tree mkd. by DeGroot
A hemlock, 15" dia., bears S.36 3/4°W., 21.0 ft., with scribe marks 1/4 S32 BT visible on a partially healed double blaze.