

TOWNSHIP 27 RANGE 02 POINT IDENTIFIER # 300200

PRIMARY CORNER DESCRIPTION Cor Secs 28, 29, 33, & 34

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GL0 resurvey by Morris Wygant, Compass man for Zachariah M. Derrick U.S. Dep. Surveyor, under contract #779, dated Feb. 7, 1908 - (DCSO records Vol. 12 Page(s) 4929)  
-----  
Set a hemlock post, 3 ft. long, 4" sq., 24" in the ground for cor. to secs. 28, 29, 32, & 33, marked T27S S 28 on NE, R2W S 33 on SE, S 32 on SW, S 29 on NW faces, with 4 notches on East & 1 notch on South edge; from which  
    A laurel, 18" dia., bears N.62°52'E., 26 lks., mkd: T27S R2W S28 BT.  
    A fir, 12" dia., bears S.57°20'E., 36 lks., mkd: T27S R2W S33 BT.  
    A fir, 12" dia. bears S.29°W., 18 lks. mkd T27S R2W S32 BT  
    A cedar, 12" dia., bears N.55°20'W., 42 lks., mkd: T27S R2W S29 BT.  
Derricks cor. for secs. 28, 29, 32, & 33, which I now destroy bears N.11°W., 360 lks.  
Note -We have no record of Derrick setting this corner.  
          JC DCSO 9/2008

Thomas E. Shrum, Jr. - For: US Plywood Corp. - Nov. 1962 - C.S. File 51/254-3  
-----  
Found - 1½" Iron pipe  
          15" cedar N.55°W., 19.1 ft. mkd: S29 BT.  
Set - 2½" Alum. cap  
          9" Cedar, N.26½°E., 40.5 ft. mkd: S28 BT.  
          44" D.Fir stump S.30°E., 61.5 ft. mkd: S33 BT.  
          48" Cedar stump S.1°W., 62.1 ft. mkd: S32 BT.

Douglas Co. Surveyors Office - Vernon "Ray" Tracy - Frank Jones - V. Perron - Sept. & Oct. 1968 - C.S. File 54/40-82  
-----  
Found - 1½" I.P. with U.S. Plywood Alum. Cap on 1" Pipe inside  
          Orig. 12", now 16" Cedar, alive, N.55°W. 27.7 ft., old scribe visible on open blaze, recorded in 1962 ren. as being 19.1 ft.  
          9" Cedar N.26½°E. 40.5 ft., nearly dead, scribe visible. 1962  
          44" D.Fir Stump S.30°E. 61.5 ft., scribe vis. 1962  
          48" Cedar stump S.1°W., 62.1 ft scribe vis.  
New - 16" D.Fir N.31°W. 24.9 ft. mkd: T27S R2W S29 CS BT  
Set - 6' steel fence post alongside aluminum cap.  
Corner falls in dense entanglement of greasewood & willow on S. side of old cat skid road.

continued next page

1

TOWNSHIP 27 RANGE 02 POINT IDENTIFIER # 300200

PRIMARY CORNER DESCRIPTION Cor Secs 28, 29, 33, & 34

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

BLM dependent resurvey by A. Bert Skeesick & Timothy J Moore, Cadastral Surveyors & Robert H Browning, Survey Technician, under Group No. 1968, surveyed Aug. 2003/July 2004 - (DCSO records Vol. 56 Page(s) 21992-3)

-----  
The cor. of secs. 28, 29, 32, and 33, remonumented by Shrum, in 1962, perpetuated by the Douglas County Surveyors Office in 1968, monumented with an iron post, 1" dia., firmly set, projecting 13" above ground, driven into an iron pipe, 2" dia., projecting 2" above ground, with aluminum cap (properly) mkd.

from which the remains of an original bearing tree  
A roothole bears S.26¾°W., 13.1 ft., with fallen fir trunk, size indeterminate, lying alongside, no marks visible. (Record, S.29°W., 11.9 ft.)

and remains of bearing trees mkd. by Shrum  
A cedar stump, 10" dia., bears N.24¾°E., 39.3 ft., with scribe marks S28 BT visible on an unhealed double blaze.

A decayed fir stump, 44" dia., bears S.31½°E., 61.1 ft., no marks visible.

A decayed cedar stump, 48" dia., bears S.1°W., 60.7 ft., no marks visible.

and bearing tree mkd. by person(s) unknown  
A cedar stump, 35" dia., bears N.69¾°W., 41.4 ft., with a healed blaze.

and new bearing trees  
A fir, 17" dia., bears N.21¾°E., 62.8 ft., mkd. T27S R2W S28 BT.

A fir, 14" dia., bears S.13½°E., 17.8 ft., mkd. T27S R2W S33 BT.

A fir, 20" dia., bears S.31½°W., 25.3 ft., mkd. T27S R2W S32 BT.

A fir, 7" dia., bears N.35¾°W., 17.0 ft., mkd. T27S R2W S29 BT.