

TOWNSHIP 27 RANGE 02 POINT IDENTIFIER # 300240

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 28 & 29

| | |
|-------------|-------------------|
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |

GLO resurvey by Morris Wygant, Compass man for Zachariah M. Derrick U.S. Dep. Surveyor, under contract #779, dated Feb. 7, 1908 - (DCSO records Vol. 12 Page(s) 4946-7)

N.0°03'W., between secs. 28 & 29
40.00 chs.

Set a Hemlock post, 3 ft. long, 4" sq., 24" in the ground, for ¼ sec. cor., marked ¼ S29 on W & 28 on E face; from which

A fir, 28" dia., bears S.60°20'E., 16 lks., mkd: ¼ S28 BT.

A fir, 10" dia., bears N.65°10'W., 23 lks., mkd: ¼ S29 BT.
44.30 chs.

Derricks ¼ sec. cor. which I now destroy, bears West, 100 lks

Note - We have no record of Derrick setting this corner.

JC DCSO 9/2008

Reported as not fd by V.R. Tracy, DCSO 12/1968 C.S. 54/40-152
Old & new logging - No trace of old BTs fd.

BLM dependent resurvey by A. Bert Skeesick & Timothy J Moore, Cadastral Surveyors & Robert H Browning, Survey Technician, under Group No. 1968, surveyed Aug. 2003/July 2004 - (DCSO records Vol. 56 Page(s) 21994)

The ¼ sec. cor. of secs 28 and 29, determined at record bearing and from the remains of an original bearing tree

A sawed fir stump, 30" dia., bears S.60°20'E., 10.6 ft., with scribe marks ¼ S28 B visible on opened blaze.

At the corner point

Set a stainless steel post, 28" long, 2½" dia., 26" in the ground, with brass cap mkd.

T27S R2W

¼
S 29 | S 28

2003

from which new bearing trees

A fir, 10" dia., bears N.16½°E., 13.8 ft., mkd. ¼ S28 BT.

A cedar, 9" dia., bears N.77¼°W., 19.1 ft., mkd. ¼ S29 BT.

Deposit a magnet in a white plastic case at the base of the stainless steel post.