

TOWNSHIP 27 RANGE 02 POINT IDENTIFIER # 300300

PRIMARY CORNER DESCRIPTION Cor Secs 20, 21, 28, & 29

| | |
|-------------|-------------------|
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |

GLO resurvey by Morris Wygant, Compass man for Zachariah M. Derrick U.S. Dep. Surveyor, under contract #779, dated Feb. 7, 1908 - (DCSO records Vol. 12 Page(s) 4947)

Set a Cedar post, 3 ft. long, 4" sq., 24" in the ground for cor. to secs. 20, 21, 28, & 29, marked T27S S 21 on NE, R2W S 28 on SE, S 29 on SW, S 20 on NW faces, with 2 notches on S & 4 notches on E edges; from which

- A cedar, 12" dia., bears N.56°40'E., 48 lks., mkd: T27S R2W S21 BT.
- A cedar, 30" dia., bears S.22°18'E., 61 lks., mkd: T27S R2W S28 BT.
- A cedar, 29" dia., bears S.20°30'W., 66 lks., mkd: T27S R2W S29 BT.
- A cedar, 12" dia., bears N.28°30'W., 93 lks., mkd: T27S R2W S20 BT.

Derricks cor. for secs. 20, 21, 28 & 29, which I now destroy bears N.19°W., 557 lks. Note: We have no record of Derrick setting this corner. JC DCSO 9/2008

Douglas Co. Surveyors Office - Milo E. Godfrey & crew - Nov. 17/18, 1964 - C.S. File 49/28-22

Found - Old, squared Cedar Stake, dim scribing visible
19" Cedar, dead on W. face, good scribing visible.
36" Cedar S.22¼°E. 40.3 ft., faint traces of old scribing visible on partly rotted face.
24" Cedar N.28½°W. 61.4 ft., No scar visible.
Cedar, uprooted & dead, S.20½°W. 43.6 ft., no scars.

Set - Brass Cap at Cor mkd: County Surveyors T27S R2W S20|S21
(Place old stake alongside) Office, 1964 S29|S28

New BTs- 8" R.Cedar N.23½°E. 24.0 ft. mkd: T27S R2W S21 CS BT
9" W.Fir S.20°E. 17.8 ft. mkd: T27S R2W S28 CS BT.
8" R.Cedar S.52°W. 6.4 ft. Mkd: T27S R2W S29 CS BT.

Note - Corner is approx. 175 ft. north of centerline Wolf Ck. access rd.

Fd. Ok Dec. 1968, V.R. Tracy, DCSO - C.S. File 54/40-138
FD. Ok by Ron Geisler, 8/1985 - M90-71

BLM dependent resurvey by A. Bert Skeesick & Timothy J Moore, Cadastral Surveyors & Robert H Browning, Survey Technician, under Group No. 1968, surveyed Aug. 2003/July 2004 - (DCSO records Vol. 56 Page(s) 21995-6)

The cor. of secs. 20, 21, 28, & 29, remonumented by the Douglas Co Surveyors Office in 1964, monumented with an iron post, 1¼" dia. firmly set, projecting 12" above ground, cont.

TOWNSHIP 27 RANGE 02 POINT IDENTIFIER # 300300

PRIMARY CORNER DESCRIPTION Cor. Secs. 20, 21, 28, & 29

| | |
|-------------|-------------------|
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |

with brass cap (properly) mkd.
from which the remains of the original bearing trees
A sawed cedar stump, 25" dia., bears N.56°E., 31.7 ft., no
marks visible on a decayed blaze. (Record, N.56°40'E.)
A sawed cedar stump, 40" dia., bears S.22°E., 40.3 ft., no
marks visible. (Record, S.22°18'E.)
A cedar, 31" dia., bears N.30°W., 69.5 ft., with a healed
blaze. (Record, N.28°30'W., 61.4 ft.)
and bearing trees mkd. by the Douglas County Surveyors Office
A cedar, 20" dia., bears N.21½°E., 23.4 ft., with a healed
blaze.
A hemlock, 15" dia., bears S.19¾°E., 17.3 ft., with
fragmentary scribe marks visible on a mostly healed
blaze.
A cedar, 14" dia., bears S.51¼°W., 6.4 ft., with
fragmentary scribe marks visible on a mostly healed
blaze.