

TOWNSHIP 27 RANGE 02 POINT IDENTIFIER # 300340

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 20 & 21

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

BLM dependent resurvey by A. Bert Skeesick & Timothy J Moore, Cadastral Surveyors & Robert H Browning, Survey Technician, under Group No. 1968, surveyed Aug. 2003/July 2004 - (DCSO records Vol. 56 Page(s) 22012-3)

-----

The 1/4 sec. cor. of secs. 20 and 21, determined at record bearing and from the remains of the original bearing trees

A sawed fir stump, 45" dia., bears N.85 1/2°E., 5.9 ft., with scribe marks 1/4 S21 B visible on fragmentary remains of the reverse of a healed blaze. (Record, N.85°30'W.)

Note: Blaze faces S.85 1/2°W.

A sawed cedar stump, 12" dia., bears S.40°W., 18.5 ft., no marks visible.

At the corner point

Set a stainless steel post, 28" long, 2 1/2" dia., 27" in the ground, with brass cap mkd.

T27S R2W

1/4

S 20 | S 21

2004

from which

A fir, 7" dia., bears S.17 3/4°E., 19.3 ft., mkd. 1/4 S21 BT.

A fir, 12" dia., bears S.60°W., 14.5 ft., mkd. 1/4 S20 BT.

Deposit a magnet in a white plastic case at the base of the stainless steel post.