

TOWNSHIP 27 RANGE 02 POINT IDENTIFIER # 300400

PRIMARY CORNER DESCRIPTION Cor Secs 16, 17, 20, & 21

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GL0 resurvey by Morris Wygant, Compass man for Zachariah M. Derrick U.S. Dep. Surveyor, under contract #779, dated Feb. 7, 1908 - (DCSO records Vol. 12 Page(s) 4949)  
-----  
Set a Fir post, 3 ft. long, 4" sq., 24" in the ground for cor. to secs. 16, 17, 20, & 21, marked T27S S 16 on NE, R2W S 21 on SE, S 20 on SW, S 17 on NW faces, with 4 notches on E & 3 notches on S edges; from which  
    A fir, 24" dia., bears N.10°40'E., 145 lks., mkd: T27S R2W S16 BT.  
    A fir, 12" dia., bears S.66°10'E., 24 lks., mkd: T27S R2W S21 BT.  
    A fir, 8" dia., bears S.22°10'W., 17 lks., mkd: T27S R2W S20 BT.  
    A fir, 24" dia., bears N.62°20'W., 21 lks., mkd: T27S R2W S17 BT.  
Derricks cor. for secs. 16, 17, 20, & 21 which I now destroy bears N.28°W., 530 lks.  
Note - We have no record of Derrick setting this corner.  
        JC DCSO 9/2008

Douglas Co. Surveyors Office - Milo E. Godfrey, Deputy - Wm. Stoffel - Mike Darby - June 1964 - C.S. File 49/28-21  
-----  
Found - D.Fir (now 14" dia.) S.22°W. 11.2 ft. Opened & found scribing on old face.  
        D.Fir (now 27" dia.) S.66°E. 15.8 ft. Good scar visible.  
        D.Fir (now 32" dia.) N.11°E., 95.7 ft. Shows scar.  
        D.Fir (now 33" dia.) N.62½°W 13.9 ft. Shows very plain axe scar.  
Set - Brass cap mkd: COUNTY SURVEYORS OFFICE 1964 T27S R2W  
  S17|S16  
  S20|S21  
  
All orig. BTs alive & in good condition.  
New BT in place of fairly dist. NE tree:  
    9" D.Fir, N.41°E., 34.7 ft. mkd: T27S R2W S16 CS BT.

Fd. Ok by V.R. Tracy, DCSO 12/1968 - C.S. File 54/40-158