

TOWNSHIP 27 RANGE 02 POINT IDENTIFIER # 300500

PRIMARY CORNER DESCRIPTION CC Secs. 9, 16 & 17

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Charles Roberts, US Deputy Surveyor under contract #759 dated Oct. 26, 1904 - (DCSO records Vol. 12 Page(s) 4891A)

Set a basalt stone 15x7x6", 11" in the ground for cor. of secs. 8, 9, 16, & 17 mkd with 4 notches on S & 4 notches on E edge, from which
A fir, 40" dia. bears N.81°E., 69 lks. mkd: T27S R2W S9 BT
A madrone, 14" dia., bears S.31°E., 47 lks., mkd: T27S R2W S16 BT.
A fir, 36" dia. bears S.56°W. 15 lks. mkd: T27S R2W S17 BT
A fir, 40" dia. bears N.19°W., 69 lks. mkd: T27S R2W S8 BT

GLO resurvey by Morris Wygant, Compass man for Zachariah M. Derrick U.S. Dep. Surveyor, under contract #779, dated Feb. 7, 1908 - (DCSO records Vol. 12 Page(s) 4915)

The cor. of secs. 8, 9, 16, & 17 which is a stone, firmly set, marked & witnessed as described by the surveyor general & which I now change to refer to **secs. 8 & 9 only.**

GLO resurvey by Morris Wygant, Compass man for Zachariah M. Derrick U.S. Dep. Surveyor, under contract #779, dated Feb. 7, 1908 - (DCSO records Vol. 12 Page(s) 4951-2)

Intersect S boundary of sec. 9, 386 lks., N.89°35'E., of cor. of secs. 8 & 9. At point of intersection I set a Fir post, 3 ft. long, 4" sq., 24" in the ground, for closing cor. of secs. 16 & 17 mkd: C C T27S R2W on S, S16 on E, S17 on W face; with 2 grooves on W & 4 grooves on E face, from which
A fir, 28" dia., bears S.16°10'E., 7 lks., mkd: T27S R2W S16 BT.
A madrone, 18" dia., bears S.25°10'W., 30 lks., mkd: T27S R2W S17 BT.

Douglas Co. Surveyors Office - Vernon "Ray" Tracy - 5/1969 - C.S. File 54/40-165

Reported as not found.
Bluffs & numerous slides in this area. No lines or BTs