

PRIMARY CORNER DESCRIPTION CC Secs. 4, 5, & 8

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO Survey by Samuel C. Flint, Under Contract #459, dated Aug. 3, 1882 (DCSO Records Vol. 12 Page(s) 4880-1)

Set Laurel post, 4 ft. long, 4" sq., 24" in the ground for cor. to secs. 4, 5, 8, & 9, marked T27S S 4 on NE, R2W S 9 on SE, S 8 on SW, S 5 on NW faces, with 5 notches on S & 4 notches on E edges; from which
 A fir, 20" dia. bears N.45°E., 30 lks. mkd: T27S R2W S4 BT
 A fir, 30" dia. bears S.30°E., 21 lks. mkd: T27S R2W S9 BT
 A fir, 30" dia. bears N.80°W., 20 lks. mkd: T27S R2W S5 BT
 No tree within limits on SW; raised stone around post.

GLO survey by Charles Roberts, US Deputy Surveyor under contract #759 dated Oct. 26, 1904 - (DCSO records Vol. 12 Page(s) 11762)

N.0°03'W., on a random line, bet. Secs. 8 & 9 - 79.36 chs Intersect E & W line, 105 lks. E of cor. of secs. 4, 5, 8, & 9. I destroy marks on post & BTs referring to secs. 8 & 9

Douglas Co. Surveyors Office - Vernon "Ray" Tracy - Frank Jones - V. Perron - Dec. 1968 - C.S. File 54/40-143

Found - Orig. 30" now 38" fir, alive, N.80°W., 13.2 ft., bark scribe visible, poor condition.
 Orig. 20" now 30" Fir, alive N.45°E., 19.8 ft. remains of axe bark blaze, no scribed or scar.
 Hole where SE BT would have been.
Set - brass cap at cor. mkd: COUNTY SURVEYORS T27S R2W OFFICE 1968 S 5 | S 4
New BTs- 8" D.Fir N.88°E., 13.0 ft. mkd: T27S R2W S4 CS BT
 7" D.Fir N.39°W., 19.5 ft. mkd: T27S R2W S5 CS BT
This corner lies on steep east slope 69.3 ft. West of CC secs. 8 & 9.

Dependent resurvey by Peter A. Peterson & Daniel L. Berry, Cadastral Surveyors, under Group No. 757, surveyed Aug./Sept. 1971 - (DCSO Records Vol. 35 Page(s) 14590-1)

The cor. of secs. 4 & 5 only, perpetuated by Tracy in 1968, monumented with an iron post, 1" dia., firmly set, protruding 12" above ground w/brass cap (properly) marked from which the orig. BTs
 A fir, 35" dia., bears N.45°E., 30 lks., no marks visible on weathered bark blaze.
 A root hole, bears S.30°E., 21 lks. with a down & decayed fir alongside, size indeterminate, no marks visible.
continued next page

TOWNSHIP 27 RANGE 02 POINT IDENTIFIER # 300600

PRIMARY CORNER DESCRIPTION CC Secs. 4, 5, & 8

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A fir, 40" dia., bears N.80°W., 20 lks., with scribe marks
BT visible on weathered bark blaze.
and trees marked by Tracy in 1968
A fir, 10" dia., bears N.88°E., 21 lks., with healed blaze
A fir, 7" dia., bears N.40°W., 30 lks, with scribe marks
T27S R2W S5 CS BT visible on partially healed blaze.

Fd. Ok by D. Edwards 3/2001 - M136-69 & C.S. 65/34-5