TOWNSHIP 27 RANGE 02 POINT IDENTIFIER # 300640

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 4 & 5

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by S.C. Flint, Contract #459, dated August 3, 1882 - (DCSO records Vol. 12 Pages 4881-2)

Set Chinquapin post, 3 ft. long, 3" sq., 24" in the ground for ¼ sec. cor. mkd; ¼ S on E & W faces, from which
A Fir, 24" dia., bears S.55°E., 10 lks., mkd: ¼ S BT.
A Laurel, 10" dia., bears N.80°W., 35 lks., mkd: ¼ S BT.

Douglas County Surveyors Office - Vernon "Ray" Tracy and crew May 1969 - C.S. File 54/40-165

Not FD - Logged & burned

Douglas Co. Surveyors Office - Randall W. Smith, Deputy - Stephen J. Flause - 1/17/2001 - C.S. File 66/19-7

NOT FOUND
Looked for corner opened numerous trees and stumps.

David Edwards - For: Roseburg Resources - 3/2001 - M 136-69 & C.S. File 65/34-5 A & B

Set - 5/8" x 48" steel pin with 2½" alum. cap.
5" dia., Fir bears N.82°E., 12.55 ft.
6" dia., Cedar bears S.23°E., 9.97 ft.
8" dia., Cedar bears S.51°W., 7.38 ft.
5" dia., Fir bears N.18°W., 6.68 ft.