

Alias \_\_\_\_\_ Description \_\_\_\_\_  
 Alias \_\_\_\_\_ Description \_\_\_\_\_  
 Alias \_\_\_\_\_ Description \_\_\_\_\_  
 Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by S.C. Flint, Contract #459, dated August 3, 1882  
 - (DCSO records Vol. 10 Page(s) 4182 Vol. 12 Pages 4881)

-----  
 Set Cedar post 4 ft. long, 4" sq., 24" in the ground for cor.  
 to secs. 4, 5, 32 and 33, marked T26S R2W S33 on NE.; T27S  
 R2W S4 on SE.; T27S R2W S5 on SW.; T26S R2W S32 on NW. faces,  
 with 4 notches on the E. and 2 on W. edges, from which  
     A Cedar 12" dia., bears N.57°E., 36 lks. dist. mkd. T26S  
     R2W S33 BT.  
     A Fir 10" dia., bears S.67°E., 28 ks. dist. mkd. T27S R2W  
     S4 BT.  
     A Fir 8" dia., bears S.35°W., 5 lks. dist. mkd. T27S R2W  
     S5 BT.  
     A Fir 40" dia., bears N.30°W., 13 lks. dist. mkd. T26S R2W  
     S32 BT.

Corner Fd. and tied in GLO survey by C.M. Collier, Deputy  
 Surveyor, under Instructions dated May/Sept. 1913 - (DCSO  
 records Vol. 10 Page(s) 4259)

Douglas County Surveyors Office - Vernon "Ray" Tracy and crew  
 July 1967 - C.S. File 54/40-34

-----  
 Found - Orig. 12" now 30" Cedar N.57°E., 23.8 ft., alive,  
           shows good scar. We do not open.  
           Orig. 10" now 18" Fir, S.67°E., 18.5 ft., alive,  
           scribe visible on opened blaze.  
           Orig. 40" now 50" Fir N.30°W., 8.6 ft., alive, shows  
           poor bark scribe "T S3 BT"  
           Orig. 8" now 12" Fir, now snag, S.40°W., (Rec.  
           S.35°W.) 3.3 ft. Open and shows "T27S R2W S5"  
           scribe.

Set Brass cap at cor. mkd:           County Surveyors Office  
                                                   S 32 | S 33   T26S  
                                                   S 5  | S 4   T27S   R2W  
                                                   1967

New BTs- 26" Cedar N.36°W., 37.1 ft. mkd. T26S R2W S32 CS BT.  
           14" Cedar N.24°E., 31.2 ft. mkd. T26S R2W S33 CS BT.  
           5" D.Fir S.59°E., 25.6 ft. mkd. S4 CS BT.  
           9" Cedar S.21°W., 21.4 ft. mkd. T27S R2W S5 CS BT.  
 Corner lies 20 ft. S. of creek, 2 ft. wide, course S.

David Edwards - For: Roseburg Resources - 3/2001 - M 136-69  
 & C.S. File 65/34-5 A & B

-----  
 Found - Brass cap.  
           11" dia., Cedar bears S.21°W., 21.4 ft.  
           continued next page

TOWNSHIP 27 RANGE 02 POINT IDENTIFIER # 300700

PRIMARY CORNER DESCRIPTION Sec. Cor. for 4 & 5; 32 & 33, T26-2

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

33" dia., Cedar bears N.36°W., 37.1 ft.  
54" dia., Fir bears N.30°W., 8.6 ft.  
New BTs- 20" dia., Cedar bears N.12°E., 39.70 ft.  
7" dia., Alder bears S.7°E., 27.15 ft.

FD. as per M136-39, By D. Edwards, 6/2010 - M160-76

Ron Rice - For: Seneca Jones Timber Co. - 5/7/2013 - C.S.  
File 65/79-9

-----  
Found - 2½" DCSO brass cap dated 1967 with the following accessories:  
12" cedar bears S.21°W., 21.4' scribing visible  
36" cedar bears N.36°W., 37.1' healed face  
54" D.Fir bears N.30°W., bark scribe no longer visible  
24" cedar bears N.12°E., 39.7' scribing visible  
7" alder bears S.7°E., 27.5' scribing visible  
Older accessories not searched for.  
Steel post adjacent to corner