

TOWNSHIP 27 RANGE 02 POINT IDENTIFIER # 336100

PRIMARY CORNER DESCRIPTION A P on So. Bdy. Sec. 33

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by S.C. Flint, Contract #459, dated August 3, 1882
- (DCSO records Vol. 12 Page(s) 4865)

Set Fir post 3 ft. long, 3" sq., 24" in the ground for
standard ¼ sec. cor. marked S C ¼ S on N. face, from which
A Fir 8" dia., bears N.70°E., 58 lks. dist. mkd. S C ¼ S
BT.
A Fir 7" dia., bears N.30°E., 64 lks. dist. mkd. S C ¼ S
BT.

GLO Resurvey by Morris Wygant, Compassman for Zachariah
Derrick, U.S. Deputy Surveyor, Under Contract #779, dated
Feb. 7, 1908 - (DCSO records Vol. 12 Page(s) 4905)

The standard ¼ sec. cor., which is a post, firmly set, mkd.
and witnessed as described by the surveyor general. I now
change this cor. to an Angle Point as follows:
Cut out all marks and remark AP on N. face; then cut out all
BTs and remark AP BT.

Douglas County Surveyors Office - Vernon "Ray" Tracy and crew
June 1969 - C.S. File 54/40-78

Found - Orig. 8" now 36" Fir, alive, N.70°E., 38.3 ft.,
shows good scars and fragmentary bark scribe.
Orig. 7" now 32" Fir, alive, N.30°E., 42.2 ft. shows
good scars.

Set brass cap at Angle Point mkd: County Surveyors Office
T27S R2W A.P.
T28S

1969

New BTs- 18" D.Fir S.66°W., 4.0 ft. mkd. "AP CS BT."
14" D.Fir N.17°W., 8.7 ft. mkd. "AP CS BT."

Call of 2½ chains to ridge top West of corner fits field
notes.