

TOWNSHIP 27 RANGE 02 POINT IDENTIFIER # 337500

PRIMARY CORNER DESCRIPTION South 1/4 Cor. Sec. 9, only

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

<p>GLO survey by Charles Roberts, US Deputy Surveyor under contract #759 dated Oct. 26, 1904 - (DCSO records Vol. 12 Page(s) 4891A)</p> <p>-----</p> <p>Set a basalt stone 12x10x7", 9" in the ground for ¼ sec. cor. mkd. ¼ on N face, from which</p> <p>    A live oak, 14" dia., bears S.60°W., 9 lks., mkd: ¼ S16 BT</p> <p>    A madrone, 8" dia., bears N.57°W., 32 lks., mkd: ¼ S9 BT.</p> <p>I destroy cor. &amp; marks on BTs made Aug. 5, 1905</p>
<p>GLO resurvey by Morris Wygant, Compass man for Zachariah M. Derrick U.S. Dep. Surveyor, under contract #779, dated Feb. 7, 1908 - (DCSO records Vol. 12 Page(s) 4915)</p> <p>-----</p> <p>West, retracing the south bdy. of sec. 9</p> <p>40.47 chs</p> <p>Intersect the ¼ sec. cor. which is a stone, firmly set, marked &amp; witnessed as described by the surveyor general &amp; which I now change to refer to sec. 9 only.</p>
<p>Douglas Co. Surveyors Office - Vernon "Ray" Tracy - 5/1969 - C.S. File 54/40-165</p> <p>-----</p> <p>Several blazed lines - No OBTs fd.</p>