

TOWNSHIP 27 RANGE 02 POINT IDENTIFIER # 340200

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 28 & 33

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO resurvey by Morris Wygant, Compass man for Zachariah M. Derrick U.S. Dep. Surveyor, under contract #779, dated Feb. 7, 1908 - (DCSO records Vol. 12 Page(s) 4928-9)

West between Secs. 28 & 33

40.00 chs

Set a Cedar post, 3 ft. long, 4" sq., 24" in the ground, for 1/4 sec. cor., marked 1/4 S28 on North and 33 on South face; from which

A Cedar, 12" dia., bears N.72°E., 23 lks., mkd: 1/4 S28 BT.

A Cedar, 30" dia., bears South, 12 lks., mkd: 1/4 S33 BT.

41.00 chs

Derricks 1/4 sec. cor. which I now destroy, bears North 400 lks

Note - We have no record of Derrick setting this corner.

JC DCSO 9/2008

Reported as not fd by V.R. Tracy, DCSO 5/1969 C.S. 54/40-165
Old Logging - dense brush no OBTs fd.

BLM dependent resurvey by A. Bert Skeesick & Timothy J Moore, Cadastral Surveyors & Robert H Browning, Survey Technician, under Group No. 1968, surveyed Aug. 2003/July 2004 - (DCSO records Vol. 56 Page(s) 21993)

Point for the 1/4 sec. cor. of secs. 28 & 33 at proportionate; there is no remaining evidence of the original cor.

Set a stainless steel post, 28 ins. long, 2 1/2" dia., 22" in the ground, with brass cap mkd. T27S R2W

1/4 $\frac{S\ 28}{S\ 33}$
2004

from which

A fir, 12" dia., bears N.24 1/2°E., 9.4 ft., mkd. 1/4 S28 BT.

A fir, 16" dia., bears S.49 1/4°E., 27.0 ft., mkd. 1/4 S33 BT.

Deposit a magnet in a white plastic case at the base of the stainless steel post.