

TOWNSHIP 27 RANGE 02 POINT IDENTIFIER # 340300

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 21 & 28

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO resurvey by Morris Wygant, Compass man for Zachariah M. Derrick U.S. Dep. Surveyor, under contract #779, dated Feb. 7, 1908 - (DCSO records Vol. 12 Page(s) 4948)

West between Secs. 21 & 28
40.10 chs
Set a hemlock post, 3 ft. long, 4" sq., 24" in the ground, for ¼ sec. cor., marked ¼ S21 on N & 28 on S face; from which
A cedar, 12" dia., bears S.71°20'W., 59 lks. mkd: ¼ S28 BT
A hemlock, 18" dia. bears N.45°30'W. 19 lks. mkd: ¼ S21 BT
41.00 chs.
Derricks ¼ sec. cor, which I now destroy, bears N.20°W. 5 chs
Note - We have no record of Derrick setting this corner.
JC DCSO 9/2008

Reported as not fd by V.R. Tracy, DCSO 12/1968 C.S. 54/40-107
Logged & burned.

BLM dependent resurvey by A. Bert Skeesick & Timothy J Moore, Cadastral Surveyors & Robert H Browning, Survey Technician, under Group No. 1968, surveyed Aug. 2003/July 2004 - (DCSO records Vol. 56 Page(s) 21996)

Point for the ¼ sec. cor. of secs. 21 & 28 at proportionate; there is no remaining evidence of the original cor.
Set an iron post, 28" long, 2½" dia., 18" in the ground, in a mound of stone, 2½ ft. diam., to top, with brass cap mkd.
T27S R2W
¼ $\frac{S\ 21}{S\ 28}$
2004

from which
A fir, 15" dia., bears N.12¼°E., 6.1 ft., mkd. ¼ S21 BT.
A fir, 14" dia., bears S.22°E., 23.3 ft., mkd. ¼ S28 BT.
Deposit a magnet in a white plastic case at the base of the iron post.