

PRIMARY CORNER DESCRIPTION South 1/4 Cor. Sec. 4 only

| | |
|-------------|-------------------|
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |

GLO Survey by Samuel C. Flint, Under Contract #459, dated Aug. 3, 1882 (DCSO Records Vol. 12 Page(s) 4880)

Set Laurel post, 3 ft. long, 3" sq., 24" in the ground, for ¼ sec. cor., marked ¼ S on N & S faces; from which
 A cedar, 20" dia., bears N.25°W., 53 lks., mkd: ¼ S BT.
 A laurel, 10" dia., bears S.83°E., 30 lks., mkd: ¼ S BT.

BLM dependent resurvey by Harold D. Corbin, Cadastral Surveyor under Group #351, surveyed July/Aug. 1957 - (DCSO records Vol. 29 Page(s) 12213-4)

The ¼ sec. cor. of sec. 4, only, determined at record bearing & dist. from the orig. SE BT as follows:

A madrone, 16" dia., bears S.83°E., 30 lks., with scribe marks ¼ S visible on opened blaze.

At the corner point

Set an iron post, 28 long, 2½" dia., 26" in the ground, with brass cap marked:

T27S R2W
 ¼ S 4
 1957

from which

A W.Pine, 6" dia., bears N.36°E., 19 lks., mkd: ¼ S4 BT.

A madrone, 13" dia., bears N.52°W., 67 lks., mkd: ¼ S4 BT.

From this point, a locally established ¼ sec. cor. of sec. 4 only, bears N.81°E., 6½ lks., monumented with a fir post, 2" cross section, 4 ft. above ground, from which

A Cedar 42" dia., bears N.25°W., 53 lks., with an opened blaze, no scribe marks visible.

Dependent resurvey by Peter A. Peterson & Daniel L. Berry, Cadastral Surveyors, under Group No. 757, surveyed Aug./Sept. 1971 - (DCSO Records Vol. 35 Page(s) 14589-90)

The ¼ sec. cor. of sec. 4 only on the N bdy of sec. 9, determined at record bearing & dist. from the remaining OBT

A madrone, 16" dia., bears S.83°E., 30 lks., with illegible scribe marks visible on opened blaze.

and trees mkd by Corbin in 1957

A W.Pine, 10" dia., bears N.36°E., 19 lks., with healed blaze.

A Madrone, 16" dia., N.52°W., 67 lks., with healed blaze.

At the corner point

Set an iron post, 28 long, 2½" dia., 23" in the ground, with brass cap marked:

¼ S 4
 T27S R2W
 1971

Cont.

PRIMARY CORNER DESCRIPTION South 1/4 Cor. Sec. 4 only

| Alias | Description |
|-------|-------------|
| Alias | Description |
| Alias | Description |
| Alias | Description |

BLM Dependent resurvey by James E. Jelley, Cadastral Surveyor under Group #351 surveyed April/May 1978 - (DCSO records Vol. 41 Page(s) 16179)

The ¼ sec. cor. of sec. 4 only, rehabilitated by Peterson & Berry, in 1971, monumented with an iron post, 2½" dia. firmly set, projecting 10" above ground, with brass (properly) mkd. from which BTs mkd. by Corbin, in 1957

A W.Pine, 10" dia., bears N.36°E., 19 lks., with healed blaze.

A Madrone, 16" dia., bears N.52°W., 67 lks., with healed blaze.

and a new BT

A fir, 8" dia., bears N.18°E., 25½ lks., mkd: ¼ S4 BT.

Kristian DeGroot, PLS 1941 - For: USFS - January 1992 - C.S. File 63/138-7

Found - 2½" IP by Peterson & Berry in 1971, firmly set, projecting 9" above ground with a 3¼" USBLM brass cap.

12"x4½ ft. high cut madrone stump bears N.49°30'W., 44.0 ft. with a healed blaze. (N.52°W., 67 lks) Corbin 1957

42" Cedar stump bears N.18°W., 34.9 ft. with a chopped open face. Unknown origin.

12" D.Fir bears N.20°E., 16.6 ft. with a healed blaze (Rec. N.18°E., 25½ lks) Peterson/Berry 1971

New BT - 14" D.Fir bears N.73°15'W. 100.00 ft scribed "¼ S4 BT"

All BTs have a 6" red band painted around the tree & the blazed face painted red. USFS sign 54-3, BEARING TREE, and sign 54-9 LAND SURVEYING MONUMENT, are nailed to all BTs. All new BTs have double blazed faces with a brass washer stamped "PLS 1941" nailed into the lower blaze. Bearings are taken to the root crown at the side & center of the tree. Bearings & distances were measured with a staff compass (Decl. 17°E) & steel tape.

FD Ok by D. Edwards, 3/2001 - M136-69 & C.S. File 65/34-5