

PRIMARY CORNER DESCRIPTION CC Secs. 9, 10, & 16

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO survey by Charles Roberts, US Deputy Surveyor under contract #759 dated Oct. 26, 1904 - (DCSO records Vol. 12 Page(s) 4889-90)

Set a basalt stone 14x9x8", 10" in the ground for cor. of secs. 9, 10, 15, & 16 mkd with 4 notches on S & 3 notches on E edge, from which

- A sugar pine, 56" dia., bears N.33°E., 129 lks., mkd: T27S R2W S10 BT.
- A hemlock, 10" dia., bears S.82°E., 118 lks., mkd: T27S R2W S15 BT.
- A fir, 36" dia bears S.52½°W. 126 lks mkd: T27S R2W S16 BT
- A fir, 30" dia. bears N.88°W., 45 lks. mkd: T27S R2W S9 BT

GLO resurvey by Morris Wygant, Compass man for Zachariah M. Derrick U.S. Dep. Surveyor, under contract #779, dated Feb. 7, 1908 - (DCSO records Vol. 12 Page(s) 4914)

The cor. of secs. 9, 10, 15, & 16 which is a stone, firmly set, marked & witnessed as described by the Surveyor General & which I now change to refer to secs. 9 & 10 only bears S. 85 lks.

BLM dependent resurvey by Harold D. Corbin, Cadastral Surveyor under Group #351, surveyed July/Aug. 1957 - (DCSO records Vol. 29 Page(s) 12207-8)

The cor. of secs. 9 & 10 only, on the N bdy of sec. 16 monumented with a basalt stone, 14x9x8", 8" above the ground, firmly set, mkd with 3 grooves on the east & 4 grooves on the south face from which the orig. BTs as follows:

blaze.

- A rotted fir stump, 36" dia., bears N.88°W., 45 lks., with no scribe marks visible.

At the corner point

Set an iron post, 28 long, 2½" dia., 26" in the ground, with brass cap marked:

T27S R2W
<u>S 9 S 10</u>
S 16
1957

from which

- A sugar pine, 62" dia., bears N.33°E., 129 lks., with scribe marks T27S R2W S10 BT visible on opened blaze.
- A dead hemlock, 15" dia., bears S.82°E., 118 lks., with opened & rotted blaze, no scribe marks visible.
- A fir, 40" dia., bears S.52½°W., 126 lks., with a healed

continued next page

TOWNSHIP 27 RANGE 02 POINT IDENTIFIER # 378500

PRIMARY CORNER DESCRIPTION CC Secs. 9, 10, & 16

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A W.Fir, 13" dia., bears N.33°E., 65 lks., mkd: T27S R2W S10 BT.
A fir, 13" dia., bears S.26½°W., 40 lks., mkd: T27S R2W S16 BT.
A fir, 18" dia. bears N.20°W., 62 lks. mkd: T27S R2W S9 BT
Deposit orig. cor. stone alongside iron post.
Lat & long per plat:
Latitude 43°13.7'N
Longitude 122°55.8'W

Douglas Co. Surveyors Office - Vernon "Ray" Tracy - Dec. 1968 - C.S. File 54/40-154

FD. BC.
South CC Secs. 15 & 16, bears N.88¾°E., 142.4 ft.