

TOWNSHIP 27 RANGE 02 POINT IDENTIFIER # 400100

PRIMARY CORNER DESCRIPTION C C for Secs. 33 & 34 only (South)

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

GLO Resurvey by Morris Wygant, Compassman for Zachariah Derrick, U.S. Deputy Surveyor, Under Contract #779, dated Feb. 7, 1908 - (DCSO records Vol. 12 Page(s) 4939)

Intersect South bdy. of Tp. 265 lks. N.87°57'E. of old cor. for secs. 33 & 34, which I have previously changed to an angle point.

At point of intersection, I Set a Fir post 3 ft. long, 4" sq., 24" in the ground for closing cor. of secs. 33 & 34, marked CC T27S R2W on N.; S33 on W.; and S34 on E.; with 3 grooves on E. and W. faces, from which

A Hemlock 14" dia., bears N.1°30'E., 66 lks. dist. mkd. T27S R2W S34 BT.

A Fir 40" dia., bears N.42°30'W., 40 lks. dist. mkd. T27S R2W S33 BT.

Survey by Ronald A. Quimby, LS 1654 and Romanso E. Ware, LS 1005 - For: U.S. Forest Service - May 1980 - M 79-45

Found - Orig. 40" now 48" D.Fir, bears N.42°30'W., 26.4 ft. with visible scribe.

Orig. 14" now 36" hemlock bears N.1°30'E., 43.6 ft. with old scar. I rescribed "CC T27S R2W S34 BT"

Set 2½" Iron pipe with brass cap mkd. "T27S R2W CC S33 S34 S3 1980 RLS 1654".

Brass washer mkd. RLS 1005 set in BT face. Also set post and sign 5.0 ft. North of corner.