

TOWNSHIP 27 RANGE 02 POINT IDENTIFIER # 400140

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 33 & 34

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO resurvey by Morris Wygant, Compass man for Zachariah M. Derrick U.S. Dep. Surveyor, under contract #779, dated Feb. 7, 1908 - (DCSO records Vol. 12 Page(s) 4938-9)

Set Hemlock post, 3 ft. long, 4" sq., 24" in the ground, for ¼ sec. cor., marked ¼ S33 on W & 34 on East face; from which
A fir, 10" dia., bears N.47°50'E., 63 lks., mkd: ¼ S34 BT.
A fir, 12" dia., bears S.11°50'W., 123 lks., mkd: ¼ S33 BT
Derricks ¼ sec cor. which I now destroy bears N.22°E. 310 lks
Note - We have no record of Derrick setting this corner.
JC DCSO 8/2008

Ronald A. Quimby, LS #1654 & Romanso E. Ware, LS #1005 - For: US Forest Service - May 1980 - M79-45

Found - 3/4" Iron pipe with alum. cap in mound of stone mkd: "USPC PROP COR T27S R2W S33 S34 RE 4287 DO NOT DISTURB" (Not of rec)
28" Fir bears N.48°E., 42.9 ft. with visible scribe.
38" Fir bears S.17°W., 82.3 ft. with visible blaze & "X" on tree. Metal post & sign.

Kris DeGroot - 6/1998 - C.S. file 65/20-31

Found - 1¼" (O.D.) IP, firmly set, projecting 12" above a 18" x 36" mound of stone w/2½" alum. cap, properly marked. From which the OBTs
28" sawed Fir stump bears N.52°E., 42.1' w/scribe marks "4 BT" visible. (Rec. N.47°50'E, 63 lks.)
36" Fir bears S.17°W., 82.3' w/healed blaze (Rec. S.11°50'W., 123 lks)
New BT - 24" D. Fir bears S.77°30'E., 67.2', scribed "¼ S34 BT" on a double blaze w/brass washer "PLS 1941" nailed into lower blaze.
I paint a 6" red band & BT faces red & nail USFS "BEARING TREE" & "LAND SURVEY MONUMENT" signs to all BTs