

TOWNSHIP 27 RANGE 02 POINT IDENTIFIER # 400200

PRIMARY CORNER DESCRIPTION Cor Secs 27, 28, 33, & 34

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GL0 resurvey by Morris Wygant, Compass man for Zachariah M. Derrick U.S. Dep. Surveyor, under contract #779, dated Feb. 7, 1908 - (DCSO records Vol. 12 Page(s) 4927-8)

Set a Cedar post, 3 ft. long, 4" sq., 24" in the ground for cor. to secs. 27, 28, 33, & 34, marked T27S S 27 on NE, R2W S 34 on SE, S 33 on SW, S 28 on NW faces, with 1 notch on S & 3 notches on E edge; from which

- A hemlock, 32" dia., bears N.57°40'E., 64 lks., mkd: T27S R2W S27 BT.
- A cedar, 30" dia., bears S.21°E., 39 lks., mkd: T27S R2W S34 BT.
- A fir, 34" dia., bears S.21°30'W., 18 lks., mkd: T27S R2W S33 BT.
- A cedar, 30" dia., bears N.11°30'W., 12 lks., mkd: T27S R2W S28 BT.

Derricks cor. for secs. 27, 28, 33 & 34, which I now destroy bears N.19°E., 3.00 chs.

Note - We have no record of Derrick setting this corner.
JC DCSO 8/2008

Thomas E. Shrum, Jr. - For: US Plywood Corp. - Nov. 1962 - C.S. File 51/254-10

Found - 1½" iron pipe
30" cedar stump, S.21°E., 25.7 ft. rescribed S34 BT.
34" D.Fir stump, S.21½°W., 11.9 ft. rescribed S33 BT
30" Cedar stump, N.11½°W., 7.9 ft., rescribed S28 BT
36" hemlock stump, N.57½°E., 42.2 ft.

Set - 2½" alum. cap.
35" cedar stump N.17½°E., 50.5 ft. mkd: S27 Bt.

Douglas Co. Surveyors Office - Vernon "Ray" Tracy - Frank Jones - V. Perron - Dec. 1968 - C.S. File 54/40-156

Found - 1½" IP with 1" steel pipe & alum cap mis-marked for sections 27 & 28 by US Plywood. (1962)
Stumps of orig. BTs & new BT. All old stumps in place & scribe visible.

Set - 6 ft. steel fence post (Tom Shrum will correct cap)

New BTs- 4" D.Fir N.25½°E., 64.0 ft. mkd: S27 CS BT.
4" D.Fir N.73°W., 4.2 ft. mkd: S28 CS BT.
5" D.Fir S.69°E., 32.1 ft. mkd: S34 CS BT.

This corner lies in flat logged off area, growing reproduction of D.Fir, Hemlock & Cedar.

continued next page

1

TOWNSHIP 27 RANGE 02 POINT IDENTIFIER # 400200

PRIMARY CORNER DESCRIPTION Cor Secs 27, 28, 33, & 34

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

BLM dependent resurvey by A. Bert Skeesick & Timothy J Moore, Cadastral Surveyors & Robert H Browning, Survey Technician, under Group No. 1968, surveyed Aug. 2003/July 2004 - (DCSO records Vol. 56 Page(s) 21985-6)

The cor. of secs. 27, 28, 33, and 34, remonumented by Shrum, in 1962, perpetuated by the Douglas County Surveyors Office in 1968, monumented with an iron post, 1" dia., firmly set, projecting 12" above ground, with aluminum cap incorrectly mkd.

USPC PROPERTY COR

T27S R2W

27 | 28

33 | 34

RE 4287

DO NOT DISTURB

from which the remains of the original bearing trees

A sawed hemlock stump, 25" dia., bears N.56¼°E., 42.2 ft., with fragmentary scribe marks visible on a partially healed blaze. (Record, N.57°40'E.)

A sawed cedar stump, 32" dia., bears S.23½°E., 25.7 ft., with scribe marks S33 BT visible on an open blaze. (Record, S.21°E., rescribed by Shrum)

A sawed fir stump, 30" dia., bears S.22°W., 11.9 ft., with scribe marks S34 BT visible on an open blaze. (rescribed by Shrum)

A sawed cedar stump, 27" dia., bears N.14½°W., 10.0 ft., with scribe marks S28 BT visible on an open blaze. (Record, N.11°30'W., 7.9 ft., rescribed by Shrum)

from which the remains of an accessory mkd. by Shrum

A sawed cedar stump, 38" dia., bears N.15½°E., 50.0 ft., with scribe marks S27 BT visible on an open blaze.

and BTs mkd. by the Douglas County Surveyors Office

A fir, 19" dia., bears N.24½°E., 63.3 ft., with a healed blaze.

A fir, 20" dia., bears S.68¾°E., 31.7 ft., with a healed double blaze.

A fir, 20" dia., bears N.74¾°W., 4.2 ft., with a healed blaze.

and a new bearing tree

A hemlock, 12" dia., bears S.11°W., 13.0 ft., mkd. T27S R2W S33 BT.