

TOWNSHIP 27 RANGE 02 POINT IDENTIFIER # 400440

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 15 & 16

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO resurvey by Morris Wygant, Compass man for Zachariah M. Derrick U.S. Dep. Surveyor, under contract #779, dated Feb. 7, 1908 - (DCSO records Vol. 12 Page(s) 4944)

-----  
N.0°02'W., between secs. 15 & 16 @ 40.00 chs.  
Set a Fir post, 3 ft. long, 4" sq., 24" in the ground, for ¼ sec. cor., marked ¼ S16 on W & 15 on E faces; from which  
    A fir, 10" dia., bears N.14°E., 35 lks., mkd: ¼ S15 BT.  
    A fir, 20" dia., bears S.36°W., 16 lks., mkd: ¼ S16 BT.  
46.12 chs. Derricks ¼ sec. cor. which I destroy bears w. 15 lks.  
Note - We have no record of Derrick setting this corner.  
        JC DCSO 8/2008

Thomas E. Shrum, Jr. - For: US Plywood Corp. - April 1964 - C.S. File 51/254 & M29-28

-----  
Found - D.Fir 26" dia., N.14°E., 23.1 ft.  
          D.Fir 16" dia., S.36°W., 10.6 ft.  
Set - 2½" dia., alum. cap  
      Yew 16" dia., N.31½°W., 30.0 ft.  
      D.Fir 8" dia., S.74½°E., 21.9 ft.