

TOWNSHIP 27 RANGE 02 POINT IDENTIFIER # 400500

PRIMARY CORNER DESCRIPTION Closing Cor Secs. 10, 15, & 16

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GL0 survey by Charles Roberts, US Deputy Surveyor under contract #759 dated Oct. 26, 1904 - (DCSO records Vol. 12 Page(s) 4889-90)

Set a basalt stone 14x9x8", 10" in the ground for cor. of secs. 9, 10, 15, & 16 mkd with 4 notches on S & 3 notches on E edge, from which
 A sugar pine, 56" dia., bears N.33°E., 129 lks., mkd: T27S R2W S10 BT.
 A hemlock, 10" dia., bears S.82°E., 118 lks., mkd: T27S R2W S15 BT.
 A fir, 36" dia bears S.52½°W. 126 lks mkd: T27S R2W S16 BT
 A fir, 30" dia. bears N.88°W., 45 lks. mkd: T27S R2W S9 BT

GL0 resurvey by Morris Wygant, Compass man for Zachariah M. Derrick U.S. Dep. Surveyor, under contract #779, dated Feb. 7, 1908 - (DCSO records Vol. 12 Page(s) 4945)

Intersect south boundary sec. 10, 215 lks., N.89°13'E., of cor. of secs. 9 & 10
At point of intersection I set a fir post 3 ft. long, 4" sq., 242" in the ground for closing cor. of secs. 15 & 16, marked CC T27S R2W on S, S15 on E, S16 on W., faces with 3 grooves on E & W faces from which
 An Alder, 6" dia., bears S.79°20'E., 42 lks., mkd: T27S R2W S15 BT.
 A Cedar, 7" dia., bears S.55°10'W., 50 lks., mkd: ¼ S16 BT

Thomas E. Shrum, Jr. - For: US Plywood Corp. - Jan 1965 - C.S. File 51/254-23

Found - Cedar snag 16" dia., S.55°W., 33.5 ft.
Set - D.Fir snag 14" dia., S.71°E., 38.5 ft.
 W.Fir 12" dia., N.34°E., 39.1 ft.
 2½" dia., alum. cap.

Douglas Co. Surveyors Office - Vernon "Ray" Tracy - Frank Jones - V. Perron - Dec. 1968 - C.S. File 54/40-153

Found - 1½" IP with 1" pipe & US Plywood alum cap. (1965)
 Orig. 7" now 16" cedar snag, S.55°W., 33.0 ft.
 scribe visible on prev. opened blaze.
 Shrum's BT to SE, also snag.
New BTs- 10" D.Fir S.12°W., 41.2 ft mkd T27S R2W S16 CC CS BT
 13" D.Fir S.61°E., 17.6 ft mkd T27S R2W S15 CC CS BT
This corner lies on moderate N'ly slope.
South CC Secs. 9 & 10, bears S.88¾°W., 142.4 ft.

Cont.

TOWNSHIP 27 RANGE 02 POINT IDENTIFIER # 400500

PRIMARY CORNER DESCRIPTION Closing Cor. Secs. 10, 15, & 16

Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____

Romanso E. Ware - For: US Forest Service - June 1978 - M70-24 & M70-27

Found - ¾" I.R. with 2½" alum. cap mkd USPC PROPERTY CORNER

T27S R2W 16|15 RE 4287

10" D.Fir bears S.12°W., 41.2 ft. scribes visible.

16" Cedar snag S.50°W., 33 ft. scribes visible.

New BTs- 8" W.Fir bears N.81°W., 40.5 ft T27S R2W S10 CC BT

14" Maple bears S.62°E., 73.6 ft. T27S R2W S15 CC BT

Note - All new BTs mkd w/Brass or alum. washer stamped "RLS 1005" nailed to the lower blaze of tree.