

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Dennis Gaylord, USFS & Douglas Co. Deputy - Witness: Randal Lopez - Dec. 22, 1977 - C.S. File 59/42-34

Found - Orig. stone set on 7/17/1905 by Roberts. Stone is firmly set & covered with 2" of soil. Stone 16"x10"x6" is marked with 5 grooves on the south face, & 3 notches on the east edge.
A 30" Fir stump bears N.51½°W., 93.06 ft. scribing & reverse visible "T27S R2W S4 BT" - Orig. BT.
A well decomposed stump (root crown) bears N.31°E., 31.68 ft.
There are no other remaining orig. BTs. Placed a county BT sign on the stump.
A 1½" IP set by Lecklider, bears N.26°E., 1.75 ft.
3" Brass cap set by BLM bears N.42½°W., 14.70 ft. stamped: Bureau of Land Management T27S R2W S4|S3
1977 S9

Set - Referencing the corner stone, I move the stone aside & in its place I set a 2½" brass cap on a 1" gal. iron pipe. Cap stamped
County Surveyors Office T27S R2W S4|S3 1977
S9

I deposit the corner stone alongside.
Also found - BTs which were set by BLM:
16" Cedar bears N.24½°W., 81.0 ft. from this renewal. A single blaze is nearly healed over. Some scribing visible.
10" D.Fir bears N.24½°E., 46.3 ft. from this renewal. Has a single healed blaze.
Place County BT signs on both trees.
No new BTs set.

BLM Dependent resurvey by James E. Jelley, Cadastral Surveyor under Group #351 surveyed April/May 1978 - (DCSO records Vol. 41 Page(s) 16175)

The cor. of secs. 3 & 4 only, perpetuated & recorded by Gaylord, in 1977, monumented with an iron post, 1½" dia. firmly set, projecting 4" above ground, with brass cap (properly) mkd.

from which the remains of BTs mkd. by Roberts
A fir root crown, size indeterminate, bears N.31°E. 48 lks
A sawed fir stump, 26" dia., bears N.51½°W., 141 lks., with scribe marks S R2W visible on open blaze.

and BTs by Corbin
A fir, 10" dia., bears N.24°E., 70½ lks. with healed blaze
A cedar, 15" dia. bears N.25°W., 123 lks with healed blaze
continued next page

TOWNSHIP 27 RANGE 02 POINT IDENTIFIER # 400600

PRIMARY CORNER DESCRIPTION CC Secs. 3, 4, & 9

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

From this point the cor of secs 3 & 4 only, erroneously positioned by Corbin, in 1957, bears N.43°W., 0.225 chs. monumented with an iron post, 28" long, 2½" dia., firmly set 26" in the ground, mkd. & witnessed as described in the official record.

I remove the iron post.

From this same point, a point established by Lecklider, in 1959, monumented with an iron pipe, 2" dia., firmly set, projecting 2" above ground, bears N.22°E., 0.025 chs.

Kristian DeGroot - For: USFS - Jan. 1992 - C.S. File 63/138-8

Found - A 1" Iron pipe by Gaylord in 1977, firmly set, projecting 1" above ground with a 2½" brass cap. 36" rotted D.Fir stump bears N.53°45'W. 93.5 ft. with scribe marks and reverse scribe marks visible. (Rec. N.51½°W., 141 lks.) Orig. BT. 21" Cedar bears N.25°15'W., 81.4 ft. with a healed blaze. (Rec. N.24½°W., 81.0 ft. 12" D.Fir snag bears N.23°15'E., 46.6 ft. with a healed blaze. (Rec. N.24½°E., 46.3 ft.) 1½" Iron pipe firmly set projecting 6" above ground bears N.26°E., 1.70 ft.

New BT - A 6" D.Fir bears N.47°45'E., 57.8 ft. scribed "T27S R2W S3 BT"

All bearing trees have a 6" red band painted around the tree and the blazed face painted red. USFS. sign 54-3, BEARING TREE, and sign 54-9, LAND SURVEYING MONUMENT, are nailed to all BTs. All new BTs have double blazed faces with a brass washer stamped "PLS 1941" nailed into the lower blaze. Bearings are taken to the center of the tree at the root crown, and distances are measured to the root crown at the side and center of the tree. Bearings and distances were measured with a staff compass (Decl. 17°E.) and steel tape.

Fd. Ok by D. Edwards, 3/2001, M136-69 & C.S. File 65/34-5

Fd. Ok by N. Hibbs, July 2003, M142-51

Ken Hoffine - For: Patricia Sohn - Sept. 2008 - M158-17

Found - 1977 Douglas County brass cap 2" iron pipe bears N.19°48'E., 1.68 ft (record N.22°E., 1.65 ft) 23" cedar bears N.24½°E 47.6 ft (record N.24°E., 46.53 ft) healed face & tag

Down fir bears N.25½°W., 79.8 ft (record N.25°W., 81.18 ft) Corner sits at edge of maintained area for Little River Christian Camp. Also at NW corner of large culvert stockpile.

Fd as per record 4/2022- A DeGroot - M180-66