

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 3 & 4

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO Survey by Samuel C. Flint, Under Contract #459, dated Aug. 3, 1882 (DCSO Records Vol. 12 Page(s) 4880)

Set Laurel post 3 ft. long, 3" sq., 24" in the ground, for ¼ sec. cor., marked ¼ S on E & W faces; from which
A fir, 14" dia., bears S.30°E., 19 lks., mkd: ¼ S BT.
A fir, 15" dia., bears N.35°W., 65 lks., mkd: ¼ S BT.

Douglas Co. Surveyors Office - Ben B. Irving, Deputy Co. Surveyor - July 25 & 26, 1934 - (Old) Vol. 4 Pg. 17 & C.S. File 37/88

Set - 8"x10"x20" sandstone set in mound of stone. (per notes - 8"x10"x24" per map)
OBT - 36" Fir, N.35°W., 65 lks.
36" Fir, S.30°E., 19 lks.
New BT - 24" Fir, N.25°W., 77 lks.

BLM dependent resurvey by Harold D. Corbin, Cadastral Surveyor under Group #351, surveyed July/Aug. 1957 - (DCSO records Vol. 29 Page(s) 12212-3)

The ¼ sec. cor. of secs. 3 and 4, monumented with a basalt stone, 18x18x6", 10" in the ground, firmly set, marked ¼ on the S face, from which the remains of the orig BTs as follows:
A fir, 27" dia., bears S.28°E., 19 lks., with a healed blaze, also bark scribed S CS BT.
A fir stump, 42" dia., bears N.35°W., 65 lks., with scribe mark B visible on opened blaze.

At the corner point
Set an iron post, 2" long, 2½" dia., 26" in the ground with brass cap marked
T27S R2W
¼
S 4|S 3
1957

from which
A fir, 12" dia., bears N.52°E., 43 lks., mkd ¼ S3 BT.
A fir, 10" dia., bears S.81°W., 48 lks., mkd: ¼ S4 BT.
Deposit orig. cor. stone alongside iron post.

BLM Dependent resurvey by James E. Jelley, Cadastral Surveyor under Group #351 surveyed April/May 1978 - (DCSO records Vol. 41 Page(s) 16178)

The ¼ sec. cor, of secs. 3 and 4, monumented with an iron post, 2½" diam., firmly set, projecting 10" above ground, and in a mound of stone, 2 ft. base, to top, with brass cap (properly) mkd. continued next page

TOWNSHIP 27 RANGE 02 POINT IDENTIFIER # 400640

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 3 & 4

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

from which the remains of the original bearing trees
A fir, 28" dia., bears S.28°E., 19 lks., with healed lower
blaze and fragmentary scribe marks visible on upper
bark blaze.
A sawed fir stump, 42" dia., bears N.35°W., 65 lks., with
fragmentary scribe marks visible on open blaze.
and bearing trees mkd. by Corbin
A fir, 14" dia., bears N.52°E., 43 lks., with fragmentary
scribe marks visible on open blaze.
A fir, 13" dia., bears S.81°W., 48 lks., with healed
blaze.

Fd. & used on BLM Dependent resurvey by Wayne Rogers,
Cadastral Surveyor, under Group #983, surveyed May/Aug 1979 -
(DCSO records Vol. 44 Page(s) 16923-4)

FD. Ok by D. Edwards, 4/2001 - M136-69 & C.S. File 65/34-5