

TOWNSHIP 27 RANGE 02 POINT IDENTIFIER # 401600

PRIMARY CORNER DESCRIPTION CC Secs. 3, 9, & 10

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO Survey by Samuel C. Flint, Under Contract #459, dated Aug. 3, 1882 (DCSO Records Vol. 12 Page(s) 4879)

Set Maple post, 4 ft. long, 3" sq., 24" in the ground for cor. to secs. 3, 4, 9, & 10, marked T27S S 3 on NE, R2W S 10 on SE, S 9 on SW, S 4 on NW faces, with 5 notches on S & 3 notches on E edges; from which
A Maple, 8" dia. bears N.20°E. 15 lks. mkd: T27S R2W S3 BT
A fir, 36" dia. bears S.15°E. 30 lks. mkd: T27S R2W S10 BT
A Maple, 12" dia., bears S.48°W., 21 lks., mkd: T27S R2W S9 BT.
A chittem, 4" dia., bears N.16°W., 24 lks., mkd: T27S R2W S4 BT.

GLO survey by Charles Roberts, US Deputy Surveyor under contract #759 dated Oct. 26, 1904 - (DCSO records Vol. 12 Page(s) 4890A & 11761)

Intersect E and W line 106 lks. E of cor. of secs. 3, 4, 9 and 10 already described.
I destroy all marks on this cor. and bearing trees referring to secs. 9 and 10 and at point of intersection
I set a basalt stone 14x12x6 ins. 10 ins. in the ground for closing cor. of secs. 9 and 10 marked C C on S. side with 5 grooves on S and 3 grooves on E. face from which
A fir, 30" dia. bears S.80½°E. 48 lks. mkd T27S R2W S10 BT
A fir 30" dia., bears S.63°W., 120 lks. mkd T27S R2W S9 BT

Douglas Co. Surveyors Office - Ben B. Irving - Wit: James Beaty - March 9, 1929 - Old Cor. Book Pg. 81 (Also Vol. 4 Pg. 17 which is an 1934 survey by BBI w/same trees as 1929)

Identified by an old stone with 5 notches on South & 3 notched on East face. Also orig. BTs as follows:
Fir 30" dia., bears S.78°E., 31 ft. which I blaze & scribe.
Fir 30" dia., bears S.63½°W., 79 ft. which I reblaze & scribed.
Fir 24" dia., bears N.64½°W., 59 ft. which I reblazed & scribed.
New BT - 20" Fir N.14½°E., 106.7 ft. which I blazed & scribed

H.L. Eppstein by B.A. Lane - March 1935 - March 9, 1929 - Old Cor. Book Pg. 81

The two 30" fir BTs were cut by forest service in 1935. New BTs were set. Also a 2"x48" galvanized Iron pipe for corner. The new BTs are: continued next page

PRIMARY CORNER DESCRIPTION CC Secs. 3, 9, & 10

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Sugar Pine 6" dia., N.13½°E., 12.9 ft. mkd: CS S3 T27S R2W
 Fir 12" dia., bears N.74°W., 70.6 ft. mkd: CS S4 T27S R2W

BLM dependent resurvey by Harold D. Corbin, Cadastral Surveyor under Group #351, surveyed July/Aug. 1957 - (DCSO records Vol. 29 Page(s) 12209-10)

 (From the 1/4 Cor. to secs. 9 & 10)
 N.0°08'W., 40.635 chs.
 The orig. closing corner of secs 9 & 10, perpetuated by Irving in 1929, with a galvanized iron pipe, 2" dia., 18" above ground, firmly set, at record dist. from the orig. BTs, as follows:

A fir stump, 30" dia., bears S.78½°E., 48 lks., with illegible scribe marks visible on opened blaze. (Rec. bearing S.80½°E.)

A fir stump, 30" dia., bears S.63½°W., 120 lks. with scribe marks T27S 2W visible on opened blaze. (Rec. bearing S.63°W.)

and trees established by county surveyor

A fir, 10" dia., bears S.17°E., 80 lks., with scribe marks S10 T27S R2W CS visible on opened blaze.

A fir stump, 9" dia., bears S.52°W., 61 lks., with scribes marks S9 T27S R2W CS BT visible on opened blaze.

A fir, 14" dia., bears N.74°W., 108 lks., marked CS S4 T27S R2 visible on opened blaze.

40.80 chs.
 Intersect the south boundary of sec. 3, true point for closing cor. of secs. 9 & 10.

Set an iron post, 28" long, 2½" dia., 26" in the ground, with brass cap marked:

T27S R2W
 S 3
 S 9 | S 10
 CC
 1957

from which

A fir, 10" dia., bears N.4°E., 125 lks., mkd: T27S R2W S10 CC BT.

A fir, 15" dia., bears S.38°W., 172 lks., mkd: T27S R2W S9 CC BT.

From this point the cor. of secs. 3 & 4, only, on the N bdy of sec. 9 bears S.88°56'W., 123 lks.

FD. IP & 5 BTs by R. Lecklider, 7/1959 M15-30 & C.S. 51/34
 Per CS file - 1957 GLO BC bears N.1°57'E., 11.0 ft. (Also New BTs referring to this brass cap in GLO records)

continued next page

PRIMARY CORNER DESCRIPTION CC Secs. 3, 9, & 10

Alias	Description
Alias	Description
Alias	Description
Alias	Description

BLM Dependent resurvey by James E. Jelley, Cadastral Surveyor under Group #351 surveyed April/May 1978 - (DCSO records Vol. 41 Page(s) 16176-7)

N.0°21'W., bet. secs. 9 & 10
40.63 chs.

Intersect the S. bdy of sec. 3, & point for the closing cor. of secs. 9 & 10

From this point the closing cor. of secs. 9 & 10, erroneously positioned by Corbin, in 1957, bears N.0°09'W., 0.180 chs. monumented with an iron post, 28" long, 2½" dia., firmly set 26" in the ground, mkd. & witnessed as described in the official record.

I remove the iron post & at the corner point

Reset the iron post, 28" long, 2½" dia., 18" in the ground, with brass cap mkd:

T27S	R2W
S 3	
S 9	S 10
CC	
1978	
1957	

from which BTs mkd by Corbin

A fir, 14" dia., bears S.5°E., 105½ lks., with healed blaze.

A fir, 22" dia., bears S.42°W., 157 lks., with healed blaze.

From this same point, the cor. of secs. 3 & 4 only, on the N. bdy of sec. 9 bears S.88°44'W., 1.07 chs.

40.65 chs

The orig. closing cor. of secs. 9 & 10, perpetuated & recorded by Irving in 1929 & further perpetuated by Eppstein in 1935, monumented with an iron pipe, 2" dia., firmly set, projecting 2" above ground, from which the remains of the orig. BTs:

A fir stump, 30" dia., bears S.80½°E., 48 lks., with scribe marks T27S R2W S visible on opened blaze.

A fir root crown, 30" dia., bears S.63½°W., 120 lks.

and the remains of BTs mkd. by Eppstein

A pine stump 20" dia., bears N.13½°E., 20 lks., with scribes marks CS S3 T27 visible on open blaze.

A fir, 10" dia., bears S.17°E., 80 lks., with fragmentary scribe marks visible on open blaze.

A sawed fir stump, 15" dia., bears N.72½°W., 108 lks., with scribe marks CS S4 T27 S R2 visible on open blaze. (Rec. N.74°W.)