

PRIMARY CORNER DESCRIPTION A P on So. Bdy. Sec. 34

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by S.C. Flint, Contract #459, dated August 3, 1882
- (DCSO records Vol. 12 Page(s) 4866)

Set Yew post 3 ft. long, 3" sq., 24" in the ground for
standard ¼ sec. cor. mkd. S C ¼ S on N. face, from which
A Fir 18" dia., bears S.50°W., 13 lks. dist. mkd. SC ¼ S
BT.
A Fir 30" dia., bears N.10°E., 15 lks. dist. mkd. SC ¼ S
BT.

GLO Resurvey by Morris Wygant, Compassman for Zachariah
Derrick, U.S. Deputy Surveyor, Under Contract #779, dated
Feb. 7, 1908 - (DCSO records Vol. 12 Page(s) 4904)

The standard ¼ sec. cor., which is a post, firmly set, mkd.
and witnessed as described by the surveyor general, bears
North 60 lks. dist. I now change this cor. to an Angle Point
as follows:
Cut out all marks, and remark AP on N. face; then cut out all
bearing trees and remark AP BT.

Dennis Gaylord, U.S. Forest Service - Deputized by the Doug.
Co. Surveyors Office - Wit: Lee Zink - Jan. 18, 1979 - C.S.
File 60/24-6

Found - Orig. 30" now 36" Fir stump, bears N.10°E., 9.9 ft.
from face. Faint scribing visible on a bark
blaze.
Orig. 18" now 24" Fir windthrow, has double bark
blaze, but no scribing visible. This tree has
been recently chopped open. No sign of inner
face. I can tell quite accurately where this
tree stood and the original location of the face
bears S.50°W., 8.6 ft.
Referencing from the above evidence, I SET a 1½" I.P. with
a 2½" brass cap stamped: "County Surveyors Office A.P. T27S
S34 T28S S3 R2W 1979". I.P. 32" into the ground. Brass cap
is 4" above ground.
New BTs- 10" Cedar bears N.2°W., 41.6 ft. scribed "AP CS BT"
on a double blaze.
6" Yew bears N.43°E., 30.9 ft. scribed "AP CS BT" on
a double blaze.
6" Yew bears S.52°W., 47.5 ft. scribed "AP CS BT" on
a double blaze.
Placed County BT signs on all BTs.