

TOWNSHIP 27 RANGE 02 POINT IDENTIFIER # 439500

PRIMARY CORNER DESCRIPTION South 1/4 Cor. Sec. 10 only

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Charles Roberts, US Deputy Surveyor under contract #759 dated Oct. 26, 1904 - (DCSO records Vol. 12 Page(s) 4889)

Set a basalt stone 12x8x6", 9" in the ground for ¼ sec. cor. mkd. ¼ on N face, from which

 A cedar, 8" dia., bears N.54°W., 42 lks., mkd: ¼ S10 BT.

 A fir, 12" dia., bears S.27°E., 12 lks., mkd: ¼ S15 BT.

GLO resurvey by Morris Wygant, Compass man for Zachariah M. Derrick U.S. Dep. Surveyor, under contract #779, dated Feb. 7, 1908 - (DCSO records Vol. 12 Page(s) 4914)

(Retracing the south boundary of sec. 10)

The ¼ sec. cor. (which is a stone, firmly set, mkd & witnessed as described by the surveyor general, & which **I now change to refer to sec. 10 only.**)

Thomas E. Shrum, Jr. - For: US Plywood Corp. - April 1964 - M 29-27

Found - Orig. stone

 Ced. 17" dia., N.54°W., 27.7'

 D.Fir 20" dia., S.27°E., 7.9'

Romanso E. Ware - For: US Forest Service - June 1978 - M70-24 & M70-27

Found - 3/4" IR with 2½" alum cap mkd T27S R2W S10 only ¼ COR R2W, alongside orig stone See M29-27 & M29-28

 24" cedar N.55°W., 29.4 ft. visible scribes.

 28" D.Fir S.3°W., 9.1 ft. good scar.

New BT - 12" Cedar S.47°W., 10.7 ft. "¼ S10 BT" nailed alum. washer to face.

1