

TOWNSHIP 27 RANGE 02 POINT IDENTIFIER # 440100

PRIMARY CORNER DESCRIPTION So. 1/4 Cor. for Sec. 34 only

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Survey by Ronald A. Quimby, LS #1654 and Romanso E. Ware, LS #1005 - For: U.S. Forest Service - May 1980 - M 79-45

Set 2½" Iron pipe with brass cap mkd. "T27S R2W 1/4 S34 RLS 1654 1980", at proportionate location, from which
12" Cedar bears N.84°E., 19.9 ft. scribed "¼ S34 BT"
18" Fir bears S.30°W., 50.7 ft. scribed "¼ S34 BT"
Set post and sign 2.0 ft. East of corner. Brass washers mkd. "1654" set in BT faces.

Survey by Gerald V. Nygren - Oct. 1988 - C.S. File 63/69-34

Found - A 2½" Iron pipe with brass cap extending 8" above ground.
12" Cedar snag bears N.84°E., 19.9 ft., visible scribing.
18" Fir, dead and down, bears S.30°W., 50.7 ft., visible scribing.
Brass washers mkd. "RLS 1654" are set in BT faces.
New BTs- 10" Yew bears S.85°E., 81.7 ft. scribed ¼ S34 BT.
6" Yew bears S.40°W., 136.0 ft. scribed ¼ S34 BT.
Brass washers mkd. "LS 1035" and set in BT faces.