

TOWNSHIP 27 RANGE 02 POINT IDENTIFIER # 440300

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 22 & 27

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO resurvey by Morris Wygant, Compass man for Zachariah M. Derrick U.S. Dep. Surveyor, under contract #779, dated Feb. 7, 1908 - (DCSO records Vol. 12 Page(s) 4941)  
-----  
Set Hemlock post, 3 ft. long, 4" sq., 24" in the ground, for 1/4 sec. cor., marked 1/4 S22 on North and 27 on South faces; from which  
    A cedar, 16" dia., bears S.89°E., 27 lks., mkd: 1/4 S27 BT.  
    A yew, 14" dia., bears N.45°30'W., 19 lks., mkd: 1/4 S22 BT.  
Derricks 1/4 sec. cor. which I now destroy bears N.27°E., 450 lks.  
Note - We have no record of Derrick setting this corner.  
        JC DCSO 8/2008

Douglas Co. Surveyors Office - Vernon "Ray" Tracy - Nov. 1968 - C.S. File 54/40-127  
-----  
Reported as not found  
Logged & burned several years ago - no trace OBTs.

Romanso E. Ware - For: US Forest Service - June 1978 - M70-25  
-----  
Found - 3/4" iron rod, bears N.11°14'E., 28.68 ft. (no rec.)  
Set - 2 1/2" galv. IP with brass cap mkd: T27S R2W 1/4 S22 S27  
    1978 RLS 1005, in mound of stones.  
    12" Cedar S.39°E., 16.2 ft. "1/4 S27 BT"  
    12" Fir, N.58°E., 13.7 ft. "1/4 S22 BT"