

TOWNSHIP 27 RANGE 02 POINT IDENTIFIER # 440400

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 15 & 22

| | |
|-------------|-------------------|
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |

GLO resurvey by Morris Wygant, Compass man for Zachariah M. Derrick U.S. Dep. Surveyor, under contract #779, dated Feb. 7, 1908 - (DCSO records Vol. 12 Page(s) 4943)

Set Fir post, 3 ft. long, 4" sq., 24" in the ground, for ¼ sec. cor., marked ¼ S15 on N 22 on S faces; from which
A fir, 10" dia., bears S.20°50'W., 15 lks., mkd: ¼ S22 BT.
A fir, 8" dia., bears N.1°30'W., 32 lks., mkd: ¼ S15 BT.
Derricks ¼ sec. cor. which I now destroy, bears N.12°W., 500 lks.
Note - We have no record of Derrick setting this corner.
JC DCSO 8/2008

Thomas E. Shrum, Jr. - For: US Plywood Corp. - April 1964 -
C.S. File 51/254 & M29-28

Found - D.Fir 24" dia., S.18°W., down.
Set - 2½" dia., alum. cap
D.Fir 8" dia., N.36½°W., 25.2 ft.
Alder 13" dia., S.81½°E., 25.0 ft.