

PRIMARY CORNER DESCRIPTION North 1/4 Cor. Sec. 10 only

|             |                   |
|-------------|-------------------|
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |

|  |
|--|
| <p>GLO Survey by Samuel C. Flint, Under Contract #459, dated Aug. 3, 1882 (DCSO Records Vol. 12 Page(s) 4878)</p> <p>-----</p> <p>Set Dogwood post 3 ft. long, 3" sq., 24" in the ground, for 1/4 sec. cor., marked 1/4 S on N &amp; S faces; from which<br/> A fir, 8" dia., bears S.10°E., 4 lks., mkd: 1/4 S BT.<br/> A fir, 10" dia., bears N.25°W., 8 lks., mkd: 1/4 S BT.</p>  |
| <p>GLO survey by Charles Roberts, US Deputy Surveyor under contract #759 dated Oct. 26, 1904 - (DCSO records Vol. 12 Page(s) 4896 &amp; 4898)</p> <p>-----</p> <p>Pg. 4896 - (1/4 Cor.) Secs. 3 &amp; 10, witnessed as described by the Surveyor General.<br/> Pg. 4898 - 1/4 Sec. cor. which is a post, 3" sq., 1 ft. above the ground marked &amp; witnessed as described by the Surveyor General.</p>   |
| <p>Thomas E. Shrum, Jr. - For: US Plywood Corp. - Jan. 1965 - C.S. File 51/254</p> <p>-----</p> <p>Proportioned measurement<br/> Set - 2 1/2" dia., alum. cap.<br/> Hemlock, 7" dia., S.08°E., 38.1 ft.</p>  |
| <p>Fd. Ok by V.R. Tracey, DCSO, 12/1968 - C.S. File 54/40-148</p>  |
| <p>Romanso E. Ware - For: US Forest Service - June 1978 - M70-24 (See also M70-27)</p> <p>-----</p> <p>Found - 8" Hemlock, S.8°E., 38.1 ft. scribed "S10 N 1/4 BT"<br/> 3/4" IR with 2 1/2" alum cap bears S.13°23'E., 7.4' from true corner.<br/> Set - 2 1/2" IP with 3" brass cap mkd: T27S R2W 1/4 S10 1978<br/> RLS 1005, in mound of stones.<br/> Scribed- 13" W.Fir bears S.85°W., 45.7 ft. "1/4 S10 BT"</p>  |
| <p>BLM Dependent resurvey by James E. Jelley, Cadastral Surveyor under Group #351 surveyed April/May 1978 - (DCSO records Vol. 41 Page(s) 16173)</p> <p>-----</p> <p>The 1/4 sec. cor. of sec. 10 only, on the S. bdy. of sec. 3, established by Ware, in 1978, monumented with an iron post, 2 1/2" dia., firmly set, projecting 4" above ground, with alum cap mkd.<br/> T27S R2W<br/> 1/4 S10<br/> RLS No. 1005<br/> 1978</p> <p style="text-align: right;">cont. next page</p> |

PRIMARY CORNER DESCRIPTION North 1/4 Cor. Sec. 10 only

| Alias | Description |
|-------|-------------|
|       |             |
|       |             |
|       |             |
|       |             |

from which a bearing tree mkd. by Ware  
A W.Fir, 13" dia., bears S.85°W., 69 lks., with scribe marks ¼ S10 BT visible on open blaze.  
from this point, a corner established by Shrum, in 1965, bears S.14°E., 0.110 chs., monumented with an iron post, ¾" dia., firmly set, projecting 10", above ground, with alum. cap mkd.  
USP CO. PROPERTY  
T 27 S ¼ cor  
R 2 W  
Sec 10  
RE 4287  
1965

from which a bearing tree mkd. by Shrum  
A hemlock, 8" dia., bears S.8°E., 57½ lks., with scribe marks S10 N ¼ BT visible on open blaze.

BLM Dependent Resurvey by Kenneth W. Saveland, Cadastral Surveyor, under Group No. 2500, Surveyed Aug./Nov. 2011 - (DCSO records BLM Plat T27-2W 2012-1 & Vol. 58 Pages 22947-8)  
-----  
The ¼ sec. cor. of sec. 10 only, monumented with an iron post, 2½" dia., firmly set, projecting 4" above ground, with brass cap (properly) mkd.  
from which the remains of a BT mkd. by Ware PLS 1005 in 1978  
A fir snag, 23" dia., bears S.81¾°W., 36.6 ft. with a healed blaze. (Rec. S.85°W., 45.5 ft.)  
and a new BT  
A fir, 10" dia., bears S.45¾°W., 11.1 ft., mkd: ¼ S10 BT.  
From this cor., a point established by Shrum in 1965 bears S.22°03'56"E., 7.73 ft., monumented with an iron post, ¾" dia., firmly set, projecting 10" above ground, with alum. cap mkd. U.S.P.C. PROPERTY COR. T27S R2W ¼ SEC 10 RE 4287, from which the remains of a BT mkd. by Shrum  
A roothole bears S.8°E., 38.0 ft. uphill of which is a fallen hemlock trunk, 9" dia., with scribe marks / BT visible on an open blaze.

Fd. BC & BTs 6/2015 - by K Hoffine - M169-57